

FORM PTO-100 (REV 10-94)		U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE	ATTORNEY'S DOCKET NUMBER 10873.654USWO
TRANSMITTAL LETTER TO THE UNITED STATES DESIGNATED/ELECTED OFFICE (DO/EO/US) CONCERNING A FILING UNDER 35 U.S.C. 371			U.S. APPLICATION NO. (If known, see 37 CFR 1.5) Unknown 09/763385
INTERNATIONAL APPLICATION NO. PCT/JP00/04076	INTERNATIONAL FILING DATE June 21, 2000	PRIORITY DATE CLAIMED June 23, 1999	
TITLE OF INVENTION OBJECTIVE LENS FOR OPTICAL DISK, OPTICAL HEAD DEVICE AND OPTICAL INFORMATION RECORDING....			
APPLICANT(S) FOR DO/EO/US TANAKA et al.			
Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information			
<p>1. <input checked="" type="checkbox"/> This is a FIRST submission of items concerning a filing under 35 U.S.C. 371.</p> <p>2. <input type="checkbox"/> This is a SECOND or SUBSEQUENT submission of items concerning a filing under 35 U.S.C. 371</p> <p>3. <input checked="" type="checkbox"/> This express request to begin national examination procedures (35 U.S.C. 371(f)) at any time rather than delay examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) and PCT Articles 22 and 39(l).</p> <p>4. <input type="checkbox"/> A proper Demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date.</p> <p>5. <input checked="" type="checkbox"/> A copy of the International Application as filed (35 U.S.C. 371(c)(2))</p> <p>a. <input checked="" type="checkbox"/> is transmitted herewith (required only if not transmitted by the International Bureau).</p> <p>b. <input checked="" type="checkbox"/> has been transmitted by the International Bureau.</p> <p>c. <input type="checkbox"/> is not required, as the application was filed in the United States Receiving Office (RO/US)</p> <p>6. <input checked="" type="checkbox"/> A translation of the International Application into English (35 U.S.C. 371(c)(2)).</p> <p>7. <input checked="" type="checkbox"/> Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3))</p> <p>a. <input type="checkbox"/> are transmitted herewith (required only if not transmitted by the International Bureau)</p> <p>b. <input type="checkbox"/> have been transmitted by the International Bureau.</p> <p>c. <input type="checkbox"/> have not been made, however, the time limit for making such amendments has NOT expired</p> <p>d. <input checked="" type="checkbox"/> have not been made and will not be made.</p> <p>8. <input type="checkbox"/> A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).</p> <p>9. <input checked="" type="checkbox"/> An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)).</p> <p>10. <input type="checkbox"/> A translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)).</p> <p>Items 11. to 16. below concern document(s) or information included:</p> <p>11. <input type="checkbox"/> An Information Disclosure Statement under 37 CFR 1.97 and 1.98</p> <p>12. <input checked="" type="checkbox"/> An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.</p> <p>13. <input checked="" type="checkbox"/> A FIRST preliminary amendment.</p> <p><input type="checkbox"/> A SECOND or SUBSEQUENT preliminary amendment.</p> <p>14. <input type="checkbox"/> A substitute specification.</p> <p>15. <input type="checkbox"/> A change of power of attorney and/or address letter.</p> <p>16. <input checked="" type="checkbox"/> Other items or information: International Search Report; PCT Request and translation, PCT/IB/301; PCT/IB/304; PCT/IB/308</p>			

U.S. APPLICATION NO. (if known, see 37 C.F.R. 1.5)

Unknown 091/763385

INTERNATIONAL APPLICATION NO.

PCT/JP00/04076

ATTORNEY'S DOCKET NUMBER

10873.654USWO

17. [X] The following fees are submitted:

BASIC NATIONAL FEE (37 CFR 1.492(a) (1)-(5)):

Search Report has been prepared by the EPO or JPO.....\$860.00

International preliminary examination fee paid to USPTO

(37 CFR 1.492(a)(1)).....\$690.00

No international preliminary examination fee paid to USPTO (37 CFR 1.482)

but international search fee paid to USPTO (37 CFR 1.445(a)(2)).....\$710.00

Neither international preliminary examination fee (37 CFR 1.482) nor

international search fee (37 CFR 1.445(a)(3)) paid to USPTO \$1000.00

International preliminary examination fee paid to USPTO (37 CFR 1.482)

and all claims satisfied provisions of PCT Article 33(2)-(4).....\$100.00

ENTER APPROPRIATE BASIC FEE AMOUNT = \$860.00

Surcharge of \$130.00 for furnishing the oath or declaration later than [] 20 [] 30 months from the earliest claimed priority date (37 CFR 1.492(c)).

\$0

CLAIMS	NUMBER FILED	NUMBER EXTRA	RATE	
Total claims	35	-20 = 15	X \$18.00	\$270.00
Independent claims	7	-3 = 4	X \$80.00	\$320.00

MULTIPLE DEPENDENT CLAIM(S) (if applicable)

+ \$260.00

\$0

TOTAL OF ABOVE CALCULATIONS = \$1450.00

Reduction by 1/2 for filing by small entity, if applicable. Small entity status is claimed pursuant to 37 CFR 1.27

\$0

SUBTOTAL = \$1450.00

Processing fee of \$130.00 for furnishing the English translation later than [] 20 [] 30 months from the earliest claimed priority date (37 CFR 1.492(f)).

+ \$0

TOTAL NATIONAL FEE = \$1450.00

Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31). \$40.00 per property

+ \$40.00

TOTAL FEES ENCLOSED = \$1490.00Amount to be:
refunded \$0

charged \$0

a. [X] Checks in the amount of \$1450.00 and \$40.00 to cover the above fees is enclosed.

b. [] Please charge my Deposit Account No _____ in the amount of \$ _____ to cover the above fees
A duplicate copy of this sheet is enclosed.c. [X] The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No 13-2725**NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137(a) or (b)) must be filed and granted to restore the application to pending status.**

SEND ALL CORRESPONDENCE TO

Douglas P. Mueller

MERCHANT & GOULD

P.O. Box 2903

Minneapolis, MN 55402-0903

SIGNATURE: 

NAME Douglas P. Mueller

REGISTRATION NUMBER. 30,300

09/763385

S/N unknown

PATENTIN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant:	TANAKA et al.	Docket No.:	10873.654USWO
Serial No.:	unknown	Filed:	concurrent herewith
Int'l Appln No.:	PCT/IP00/04076	Int'l Filing Date:	June 21, 2000
Title:	OBJECTIVE LENS FOR OPTICAL DISK.....		

CERTIFICATE UNDER 37 CFR 1.10

'Express Mail' mailing label number: EL658341486US

Date of Deposit: February 21, 2001

I hereby certify that this correspondence is being deposited with the United States Postal Service 'Express Mail Post Office To Addressee' service under 37 CFR 1.10 on the date indicated above and is addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231.

By: 
 Name: Brian Maharaj

PRELIMINARY AMENDMENT

Box PCT
 Assistant Commissioner for Patents
 Washington, D. C. 20231

Dear Sir:

In connection with the above-identified application filed herewith, please enter the following preliminary amendment (marked-up copy attached):

IN THE SPECIFICATION

A courtesy copy of the present specification is enclosed herewith. However, the World Intellectual Property Office (WIPO) copy should be relied upon if it is already in the U.S. Patent Office.

IN THE CLAIMS

19. (Amended) An optical head device comprising two light sources, a focusing means for focusing light beams emitted from the two light sources onto an information medium surface through first and second optical disk substrates each having a thickness corresponding to

the respective light sources, a light flux separating means for separating light fluxes modulated at the information medium, and a light receiving means for receiving the light beams modulated at the information medium, wherein the focusing means is the objective lens for an optical disk according to claim 1.

REMARKS

The above preliminary amendment is made to remove multiple dependencies from claim 19.

Applicants respectfully request that the preliminary amendment described herein be entered into the record prior to calculation of the filing fee and prior to examination and consideration of the above-identified application.


If a telephone conference would be helpful in resolving any issues concerning this communication, please contact Applicants' primary attorney-of record, Douglas P. Mueller (Reg. No. 30,300), at (612) 371.5237.

Respectfully submitted,

MERCHANT & GOULD P.C.
P.O. Box 2903
Minneapolis, Minnesota 55402-0903
(612) 332-5300

Dated: February 21, 2001

By



Douglas P. Mueller
Reg. No. 30,300

DPM/tvm

MARKED-UP COPY

19. (Amended) An optical head device comprising two light sources, a focusing means for focusing light beams emitted from the two light sources onto an information medium surface through first and second optical disk substrates each having a thickness corresponding to the respective light sources, a light flux separating means for separating light fluxes modulated at the information medium, and a light receiving means for receiving the light beams modulated at the information medium, wherein the focusing means is the objective lens for an optical disk according to claim 1 [, 7, or 12].

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213

DESCRIPTION

OBJECTIVE LENS FOR OPTICAL DISK, OPTICAL HEAD DEVICE AND
OPTICAL INFORMATION RECORDING AND REPRODUCING

- 5 APPARATUS USING THE SAME, AND MOLD FOR MOLDING LENS,
METHOD FOR WORKING THE MOLD FOR MOLDING LENS, AND
PROFILE MEASURING DEVICE FOR MEASURING PROFILE OF THE
MOLD FOR MOLDING LENS

10 Technical Field

The present invention relates to an objective lens for an optical disk
used in an optical head for a digital video disk, a digital audio disk, an optical
memory disk for a computer, and the like. In particular, the present
invention relates to an objective lens for an optical disk including a single lens
and capable of satisfying an excellent light focusing property in accordance
with any two kinds of optical disks each having a different thickness, an
optical head device and an optical information recording and reproducing
device using the same, and a mold for molding an objective lens, a method for
working the mold and a profile measuring device for measuring the profile of
the mold.

20 Background Art

In general, an optical head device for an optical disk often employs a
single lens having an aspheric surface as an objective lens for recording or
reproducing information by focusing light beams into a diffraction limited
point image on an information medium. However, in recent years, it is
increasingly required to reproduce data compatibly with optical disks each
having a different thickness. For example, it is required to read a CD
(compact disk) or a CD-ROM having a disk thickness of 1.2 mm and a DVD
(digital versatile disk) or DVD-ROM having a disk thickness of 0.6 mm by a
single optical head. In this case, one method is to use two objective lenses,
one lens corresponding to and one lens corresponding to the CD or CD-ROM
having a disk thickness of 1.2 mm and one lens corresponding to the DVD or
DVD-ROM having a disk thickness of 0.6 mm. However, from the viewpoint
of simplifying an optical system, it is advantageous to use a single lens that is
applicable for two kinds of optical disks each having a different thickness. In
other words, in the optical head using two objective lenses, since a mechanism

for switching lenses is needed, the configuration of the optical head becomes complicated, thus making it difficult to achieve a small size and low cost. Furthermore, it is desirable that the objective lens be as simple as possible.

For example, in JP8 (1996)-334690A and JP9 (1997)-184975A, a so-called two-zone divided type lens is disclosed as an objective lens in order to attain the above-mentioned object. In this configuration, a lens is divided into two regions, in which an inner circumference portion is designed to be suitable for use with a CD or CD-ROM, and an outer circumference region is designed to be suitable for use with a DVD or DVD-ROM. Hereinafter, a conventional objective lens will be described with reference to Fig. 28. Fig. 28 is a view of an arrangement showing a relationship between an objective lens and an optical disk in the prior art.

Fig. 28(a) is a view showing an optical path of a two-sided aspheric objective lens 33 when a light beam is focused onto an optical disk 32 having a thickness of 0.6 mm. The surface of the objective lens at the side of the light source includes an outer circumference region 34 and an inner circumference region 35. In the outer circumference region 34, the spherical aberration is corrected with respect to the optical disk 32 having a thickness of 0.6 mm. On the other hand, in the inner circumference region 35, the spherical aberration is corrected with respect to the optical disk having a thickness of 0.9 mm. The boundary between the inner circumference region 35 and the outer circumference region 34 is determined by the NA that is necessary to reproduce data of the disk having a thickness of 1.2 mm for a light source of a wavelength of 655 nm. For example, when an optical disk having a thickness of 1.2 mm is reproduced at a wavelength of 780 nm and a NA of 0.45, the NA of the light source of 655 nm is about 0.37. The inner circumference region 35 has a spherical aberration with respect to the optical disk having a thickness of 0.6 mm. Herein, the total aberration is much smaller than 0.07λ (which is called a diffraction limit) and falls in a sufficient aberration for reproducing the optical disk of a thickness of 0.6 mm.

Fig. 28(b) is a view showing an optical path when a light beam is focused onto an optical disk 36 having a thickness of 1.2 mm by using the same objective lens 33. Since the inner circumference region 35 of the same objective lens 33 is optimized with respect to an optical disk having a thickness of 0.9 mm, the aberration is small for the optical disk 36 having thickness of 1.2 mm. However, since the outer circumference region 34 is optimized with respect to an optical disk 32 having a thickness of 0.6 mm, the

aberration is large for the optical disk 36 having a thickness of 1.2 mm, so that it does not contribute to the light focusing. Therefore, the outer circumference region 34 also functions as an aperture.

When there is one light source, under the above-mentioned conditions, sufficient performance with respect to two kinds of optical disks each having a thickness of 0.6 mm and 1.2 mm respectively can be attained. However, when it is necessary to reproduce the optical disk having a thickness of 1.2 mm by using the light source of 780 nm like CD-R, the wavelength becomes longer. Consequently, it is necessary to increase the NA relatively, so that the aberration with respect to the optical disk having a thickness of 0.6 mm becomes larger, thus deteriorating the focusing property.

Furthermore, not shown in Fig. 28, a mold for molding an objective lens with a difference in level between an inner circumference portion and an outer circumference portion has been produced by cutting with the use of a diamond cutting tool in order to precisely work a portion having the difference in level.

Furthermore, in a profile measuring device for measuring and evaluating the worked mold, a rotationally symmetric aspheric surface is used as design profile data which is reference data for evaluating measurement values. When a zone-divided type objective lens is measured, the inner circumference portion and the outer circumference portion are measured separately, or a fitting of the profiles of the inner circumference portion and the outer circumference portion is carried out by the use of a higher order aspheric coefficient of about 20-th order to express the profile and the profile is compared with the measurement values.

When the above-mentioned zone-divided type objective lens has the portion having the difference in level between an aspheric surface of the inner circumference portion and an aspheric surface of the outer circumference portion, an ideal design is to provide a surface forming the difference in level approximately parallel to the optical axis. However, in actual working, it is necessary to weaken the surface forming the difference in level to such an extent that the portion having the difference in level can be worked. JP 9 (1997)-184975A discloses the profile in which the portions having the difference in level are smoothly connected. However, it is a profile in which an aspheric surface of the inner circumference portion and an aspheric surface of the outer circumference portion are weakened approximately uniformly. Such a profile can be obtained only by cutting with the use of a cutting tool.

Herein, in cutting with the use of the cutting tool, there is a limitation on the type of metal material that can be worked. Unless a relatively soft metal having excellent cutting properties is used, a sufficient working accuracy cannot be obtained. On the other hand, for press molding the lens from a glass material, it is necessary to mold the lens at high temperature and high pressure. It is desirable that a metal material having high hardness, such as a cemented carbide (a sintered metal including WC as a main component) is used. However, the cemented carbide cannot be worked by cutting with the use of cutting tool. In other words, the zone-divided type objective lenses, which have been proposed to date, have a profile for plastic molding. Therefore, most of the conventional objective lenses molded by the use of glass materials have a difficulty in working a mold.

Furthermore, the refractive index of the lens using a plastic material is changed greatly due to a change in temperature. For example, in an optical head device that is necessary to secure operation in a wide range of temperatures, for example, for vehicle apparatus, in general, glass lens is used. However, as mentioned above, a zone divided type DVD/CD compatible lens is designed based on plastic molding. Thus, the temperature characteristics are extremely deteriorated.

Furthermore, in a profile measuring device for measuring and evaluating a mold for molding a lens, the measured profile and the preliminary stored design profile are compared with each other and a working error is calculated. However, a design profile that can be input is only a profile such as a rotationally symmetric aspheric surface. In the method for measuring the zone divided type objective lens by separating the inner circumference portion and the outer circumference portion, since the entire area of the lens is not measured at one time, it is impossible to know the error in profile exactly. Furthermore, in the method of measuring the profile of the entire lens by expressing the profile of the entire lens by fitting with the use of a higher order aspheric coefficient and using this aspheric profile as a design profile, the fitting error occurs around the portion having the difference in level, and thus sufficient measuring accuracy cannot be obtained.

Disclosure of Invention

It is an object of the present invention to provide an objective lens for an optical disk including one lens and capable of satisfying an excellent focusing property in accordance with any optical disks each having a different

thickness, an optical head apparatus and an optical information recording and reproducing device using the same. It is another object of the present invention to provide a zone-divided type objective lens made of a glass material and excellent in productivity. It is a further object of the present invention to provide a mold for molding the zone-divided type objective lens using cemented carbide capable of being resistant to the molding of glass materials and a method for working the mold. It is a still further object of the present invention to provide a profile measuring device capable of evaluating the profile of the mold for molding the zone-divided objective lens exactly.

In order to achieve the above-mentioned objects, a first configuration of an objective lens for an optical disk according to the present invention includes a single lens having aspheric surfaces on both sides and focusing light beams into a point image through first and second optical disk substrates each having a different thickness, at least one aspheric surface including two regions of an inner circumference region at the inner side of a circular aperture having an optical axis as a center and an outer circumference region located on an outer side with respect to the inner circumference region, the aspheric profile of the outer circumference region correcting a spherical aberration with respect to the first optical disk substrate having a smaller thickness among the first and second optical disk substrates, the aspheric profile of the inner circumference region correcting a spherical aberration with respect to the second optical disk substrate having a larger thickness, and the outer circumference region and the inner circumference region are in contact with each other at the boundary therebetween with a difference in level in the direction of the optical axis, wherein the objective lens satisfies the following relationships (1) to (4);

$$t_1 < t_2 \quad (1)$$

$$0.05 < TW < 0.12 \quad (2)$$

$$0.38 < NA_1 < 0.46 \quad (3)$$

$$0.1 < p(n-1)/\lambda < 0.6 \quad (4)$$

wherein t_1 denotes a thickness of the first optical disk substrate, t_2 denotes a thickness of the second optical disk substrate, NA_1 denotes a NA of the objective lens at the aperture of the inner circumference region, TW denotes a wavefront aberration when light beams are focused through the first optical disk substrate (unit is λ : rms), n denotes a refractive index of the objective lens at the wavelength of a light source when data of the first optical disk are

reproduced, p denotes a difference in level between the inner circumference region and the outer circumference region in the direction of the optical axis; and λ denotes a wavelength of the light source when data of the first optical disk are reproduced.

According to the first configuration of the objective lens for an optical disk, it is possible to obtain an excellent focusing spot with respect to the first optical disk and the second optical disk with one lens. As a result, excellent recording and reproducing characteristics can be obtained.

Furthermore, it is preferable in the first configuration of the objective lens for an optical disk of the present invention that the third order spherical aberration component $S3$ of the wavefront aberration is approximately 0 when light beams are focused through the first optical disk substrate. According to this preferable configuration, it is possible to minimize the deterioration in performance with respect to an error in the substrate thickness of the optical disk.

Furthermore, it is preferable in the first configuration of the objective lens for an optical disk of the present invention that a fifth order spherical aberration component $S5$ (unit is λ :rms) of the wavefront aberration satisfies the following relationship (5) when light beams are focused through the first optical disk substrate.

$$-0.03 < S5 < 0.03 \quad (5)$$

According to this preferable configuration, it is possible to suppress the light focusing property, in particular, the peak intensity of an Airy ring when the first optical disk is reproduced. Consequently, the deterioration of the reproducing characteristics of the optical disk can be prevented.

Furthermore, it is preferable in the first configuration of the objective lens for an optical disk of the present invention that the thickness $t3$ of the optical disk substrate satisfies the following relationship (6), when the aspheric profile of the inner circumference region is optimized so that the spherical aberration is corrected with respect to the thickness $t3$ of the optical disk substrate.

$$0.8 < t3 < 1.2 \quad (6)$$

According to this preferable configuration, it is possible to suppress the deterioration factor of the focusing spot for the first optical disk and to reduce the recording density of the second optical disk as compared with the first optical disk so as to reduce the effect of the coma aberration by the tilt of the second optical disk and to suppress the deterioration factor other than the

spherical aberration.

Furthermore, it is preferable in the first configuration of the objective lens for an optical disk of the present invention that the cross section of the portion having the difference in level between the inner circumference region and the outer circumference region has a circular arc profile. According to this preferable configuration, working by using a cutting tool, a grindstone, or the like, can be carried out easily.

Furthermore, it is preferable that the first configuration of the objective lens for an optical disk of the present invention is formed by glass molding or plastic molding. According to this preferable configuration, it is possible to cheaply mass-produce lenses having the same profiles and the same performances by previously working a mold of the aspheric profile.

Furthermore, a second configuration of an objective lens for an optical disk according to the present invention includes a single lens having aspheric surfaces on both sides and focusing light beams into a point image through first and second optical disk substrates each having a different thickness, at least one aspheric surface including three regions composed of an inner circumference region at the inner side of a circular aperture having an optical axis as a center, a middle region located at an outer side with respect to the inner circumference region and surrounded by another circular aperture that is located at an outer side of the circular aperture, and an outer circumference region located at an outer side with respect to the middle region, the aspheric profiles of the inner circumference region and the outer circumference region correcting a spherical aberration with respect to the first optical disk substrate having a smaller thickness among the first and second optical disk substrates, and the aspheric profile of the middle region correcting a spherical aberration with respect to an optical disk substrate having a thickness that is larger than the thickness of any of the first and second optical disk substrates, wherein the objective lens for an optical disk satisfies the following relationships (7) and (8);

$$0.35 < NA_2 < 0.43 \quad (7)$$

$$0.03 < NA_3 - NA_2 < 0.1 \quad (8)$$

wherein NA_2 denotes a NA of the objective lens at the boundary between the inner circumference region and the middle region, and NA_3 denotes a NA of the objective lens at the boundary between the middle region and the outer circumference region.

According to the second configuration of the objective lens for an

optical disk, it is possible to obtain an excellent focusing spot with respect to the first optical disk and the second optical disk with one lens. As a result, excellent recording and reproducing characteristics can be obtained.

Furthermore, it is preferable in the second configuration of the objective lens for an optical disk of the present invention that the thickness t_4 of the optical disk substrate satisfies the following relationship (9), when the aspheric profile of the middle region is optimized so that the spherical aberration is corrected with respect to the thickness t_4 of the optical disk substrate.

$$1.4 < t_4 < 2.0 \quad (9)$$

According to this preferable configuration, it is possible to correct an aberration with respect to the second optical disk excellently.

Furthermore, it is preferable in the second configuration of the objective lens for an optical disk of the present invention that either the boundary in which the inner circumference region is connected to the middle region or the boundary in which the middle region is connected to the outer circumference region does not have a difference in level. According to this preferable configuration, it is possible to secure the quantity of light by reducing the ineffective portion occurring at the time of working a lens and to suppress the deterioration of the light focusing property.

Furthermore, it is preferable in the second configuration of the objective lens for an optical disk of the present invention that the cross section of the portion having a difference in level between the inner circumference region and the middle region or the cross section of the portion having a difference in level between the middle region and the outer circumference region has a circular arc profile.

Furthermore, it is preferable in the second configuration of the objective lens for an optical disk of the present invention that the objective lens is formed by glass molding or plastic molding.

Furthermore, a third configuration of an objective lens for an optical disk according to the present invention includes a single lens having aspheric surfaces on both sides and focusing light beams into a point image through first and second optical disk substrates each having a different thickness, at least one aspheric surface including three regions composed of an inner circumference region at the inner side of a circular aperture having an optical axis as a center, a middle region located at an outer side with respect to the inner circumference region and surrounded by another circular aperture that

is located at an outer side of the circular aperture, and an outer circumference region located at an outer side with respect to the middle region, the aspheric profiles of the inner circumference region and the outer circumference region correcting a spherical aberration with respect to the first optical disk substrate having a smaller thickness than the second optical disk substrate, the thickness t_5 of the optical disk substrate satisfies the following relationship (10) when the aspheric profile of the middle region is optimized so that the spherical aberration is corrected with respect to the thickness t_5 of the optical substrate, and the outer circumference region is formed with a difference in level corresponding to an integral multiple of the optical path length in the direction of an axis with respect to the inner circumference region, wherein the objective lens satisfies the following relationships (11) to (13).

$$\begin{aligned} 1. \quad 0 < t_5 < 1.4 & (10) \\ t_1 < t_2 & (11) \\ 0.35 < NA_2 < 0.43 & (12) \\ 0.03 < NA_3 - NA_2 < 0.1 & (13) \end{aligned}$$

wherein t_1 denotes a thickness of the first optical disk substrate, t_2 denotes a thickness of the second optical disk substrate, NA_2 denotes a NA of the objective lens at the boundary between the inner circumference region and the middle region, and NA_3 denotes a NA of the objective lens at the boundary between the middle region and the outer circumference region.

According to the third configuration of the objective lens for an optical disk, it is possible to obtain an excellent focusing spot with respect to the first optical disk and the second optical lens with one disk. As a result, excellent recording and reproducing characteristics can be obtained.

Furthermore, it is preferable in the third configuration of the objective lens for an optical disk of the present invention that the focal position in which a wavefront aberration of the inner circumference region is minimized and the focal position in which a wavefront aberration of the outer circumference region is minimized are the same when light beams are focused through the second optical disk substrate. According to this preferable configuration, when light beams reflected from an information medium surface are incident in a photodetector, they return to the same portions with respect to the inner circumference region and the outer circumference region. As a result, it is possible to obtain an accurate signal light.

Furthermore, it is preferable in the third configuration of the objective

lens for an optical disk of the present invention that the third order spherical aberration component S3 of the wavefront aberration in the ranges of the inner circumference region and the middle region is approximately 0 when light beams are focused through the second optical disk substrate. According to this preferable configuration, it is possible to record and reproduce the second optical disk excellently.

Furthermore, it is preferable in the third configuration of the objective lens for an optical disk of the present invention that the boundary in which the inner circumference region is connected to the middle region does not have a difference in level.

Furthermore, it is preferable in the third configuration of the objective lens for an optical disk of the present invention that the boundary between the middle region and the outer circumference region is provided at the intersection point of the profiles of the middle region and the outer circumference region. Furthermore, it is preferable in the third configuration of the objective lens for an optical disk of the present invention that both the boundary in which the inner circumference region is connected to the middle region and the boundary in which the middle region is connected to the outer circumference region do not have a difference in level. According to such a preferable configuration in which the boundary between the middle region and the outer circumference region is provided at the intersection point of the profiles of the middle region is connected to the outer circumference region and both the boundary in which the inner circumference region is connected to the middle region and the boundary in which the middle region is connected to the outer circumference region do not have a difference in level, it is possible to facilitate the work by removing a portion having the difference in level from the aspheric profile and to suppress the loss of the quantity of light by removing the ineffective region from the surface profile.

Furthermore, it is preferable in the third configuration of the objective lens for an optical disk of the present invention that the objective lens is produced by glass molding or plastic molding.

As mentioned above, in the first to third configurations of the objective lens for an optical disk of the present invention, the aberration correction of a single lens is designed so as to obtain a focusing performance necessary to the substrate thickness of two optical disks, respectively. In the aberration of the lens having a smaller thickness of the optical disk substrate and a higher NA, since it is necessary to take the aberration at the optical disk having a

large thickness into account, the total aberration becomes larger than is conventional. However, in this aberration, by designing the different profiles in the outer circumference region and the inner circumference region, and at the same time by providing the boundary between the outer circumference region and the inner circumference region with the surface forming the difference in level in the direction of the optical axis, it is possible to maintain the profile of the spot at the side of the optical disk in which information is recorded with a high density. Furthermore, in the aberration of the lens having a larger thickness of the optical disk substrate and lower recording density and lower NA, by suppressing the aberration in the necessary aperture sufficiently and deteriorating the aberration rapidly at the outside of the necessary aperture, it is possible to provide the same effect as having a diaphragm. As a result, it is possible to record information or reproduce information with a stable performance.

Furthermore, a first configuration of an optical head device according to the present invention includes two light sources, a focusing means for focusing light beams emitted from the two light sources onto the information medium surface through first and second optical disk substrates each having a thickness corresponding to the respective light source, a light flux separating means for separating light fluxes modulated at the information medium, and a light receiving means for receiving the light beams modulated at the information medium, wherein the focusing means is one of the first to third configurations of the objective lens for an optical disk according to the present invention.

Furthermore, a configuration of an optical information recording and reproducing apparatus according to the present invention, recording information on the information medium of surfaces of the first and second optical disk substrates each having a different thickness, or reproducing information recorded on the information medium surfaces by the use of an optical head device, wherein the first configuration of the optical head device according to the present invention is used as the optical head device.

According to the first configuration of the optical head device and the configuration of the optical information recording and reproducing apparatus, since it is possible to record and reproduce information with one objective lens with respect to two kinds of optical disks each having a different substrate thickness, a cheap optical head device and optical information recording and reproducing apparatus can be realized. Furthermore, by providing any of the

optical disks with aberration suitable to each disk in accordance with the aperture of the objective lens, it is possible to obtain an excellent recording, reproducing and erasing performance with respect to the two kinds of optical disks with one objective lens.

Furthermore, a fourth configuration of an objective lens for an optical disk according to the present invention includes a single lens made of glass and which focuses light beams into a point image through first and second optical disk substrates each having a different thickness, at least one surface is divided into at least three regions by concentric circles having an optical axis as a center, and among the three regions, a first region including the optical axis and a second region located at an outermost part are rotationally symmetric aspheric surfaces, and a third region sandwiched by the first region and the second region is a toric surface having the optical axis as an axis of rotation. According to the fourth configuration of the objective lens for an optical disk, various advantageous are provided as compared with a conventional two-zone divided type objective lens having a sharp difference in level. In other words, since the conventional objective lens has a sharp difference in level, it is required that the mold must be worked by the use of a diamond cutting tool. As a result, material to be molded is limited. However, according to the fourth configuration of the objective lens for an optical disk, since a portion having a difference in level is formed by the toric surface having the optical axis as an axis of rotation, it is possible to work the mold with a grindstone. Thus, it is possible to produce a lens by using a glass material to be molded at high temperature and high pressure.

Furthermore, it is preferable in the fourth configuration of the objective lens for an optical disk of the present invention that the third region that is the toric surface is in contact with the second region and intersects the first region.

Furthermore, it is preferable in the fourth configuration of the objective lens for an optical disk the present invention that aspheric coefficients of the first region and the second region are different from each other.

Furthermore, it is preferable in the fourth configuration of the objective lens for an optical disk of the present invention that the toric surface is provided on the surface having a larger central radius of curvature of the lens.

Furthermore, it is preferable in the fourth configuration of the objective lens for an optical disk of the present invention that the third region

is a toric surface obtained by rotating a circular arc with an optical axis as a center, the circular arc having a radius R satisfying the following relationship (14).

$$0.7 \text{ mm} < R < 2.5 \text{ mm} \quad (14)$$

When R is 0.7 mm or less, a mold cannot be worked by grinding work, thus making it difficult to produce the lens. On the other hand, when R is 2.5 mm or more, the width of the arc circular portion is too broad, thus deteriorating the performance of the lens.

Furthermore, it is preferable in the fourth configuration of the objective lens for an optical disk of the present invention that the third region is a toric surface obtained by rotating a circular arc with an optical axis as a center, the circular arc having a radius R satisfying the following relationship (15).

$$1.6 \text{ mm} < R < 2.1 \text{ mm} \quad (15)$$

Furthermore, it is preferable in the fourth configuration of the objective lens for an optical disk of the present invention that the width w of the third region satisfies the following relationship (16).

$$0.02 \text{ mm} < w < 0.04 \text{ mm} \quad (16)$$

When w is 0.02 mm or less, the lens has a profile that cannot be worked by using a grindstone, thus making it difficult to produce the lens. On the other hand, when w is 0.04 mm or more, the difference in profile between an actually obtained lens and an ideally designed lens is too large, and thus sufficient lens performance cannot be exhibited.

Furthermore, a second configuration of the optical head device according to the present invention includes a first light source emitting light beams having a first wavelength, a second light source emitting light beams having a second wavelength different from the first wavelength, a focusing means for focusing light beams from the first and second light sources onto an information recording medium, a first light receiving means for receiving the light beams having the first wavelength among the reflecting light beams from the information recording medium and a second light receiving means for receiving the light beams having the second wavelength, wherein the focusing means is the fourth embodiment of the objective lens for an optical disk according to the present invention.

According to the second configuration of the optical head device, since the fourth configuration of the optical lens for an optical disk of the present invention is used, it has the following advantageous over the optical head

device using the conventional zone-divided type objective lens. Namely, since the fourth embodiment of the objective lens for an optical disk of the present invention is an objective lens made of a glass material having less deterioration in the aberration due to a change in temperature, for example, it is possible to realize an optical head device necessary to secure an operation under a wide range of temperature conditions, for example, for a vehicle apparatus, etc. Furthermore, as mentioned above, the production cost of the mold can be reduced as compared with a conventional objective lens, and furthermore, a longer lifetime of the mold is expected to be attained.

Consequently, it is possible to reduce the production cost of an objective lens and in turn the production cost of the optical head device.

Furthermore, a configuration of a mold for molding a lens according to the present invention is as follows. The mold is produced by grinding cemented carbide. A lens molding surface is divided into at least three regions by concentric circles having an optical axis as a center, and among the three regions, a first region including the optical axis and a second region located at an outermost part are rotationally symmetric aspheric surfaces, the third region which is sandwiched by the first region and the second region is a toric surface having the optical axis as an axis of rotation. According to the configuration of the mold for molding the lens, various advantages are obtained over the conventional two-zone divided type objective lens, because a portion having a difference in level is formed of the toric surface having the optical axis as an axis of rotation. Namely, production by using the grindstone is possible and a super-hard material suitable for molding a glass material can be used as a material for the mold. Furthermore, since there is no roughness having a small vertex radius of curvature within an effective diameter, it is possible to carry out profile measuring at high accuracy by the use of a probe having a tip radius of curvature of about 500 μ m.

Furthermore, it is preferable in the configuration of the mold for molding the lens of the present invention that the radius of curvature R of the toric surface having the optical axis as an axis of rotation satisfies the following relationship (17).

$$0.7 \text{ mm} < R < 2.5 \text{ mm} \quad (17)$$

Furthermore, it is preferable in the configuration of the mold for molding the lens of the present invention that the radius of curvature R of the toric surface having the optical axis as an axis of rotation satisfies the following relationship (18).

$$1. \quad 6 \text{ mm} < R < 2. \quad 1 \text{ mm} \quad (1 \ 8)$$

If a grindstone having a radius that is the same as or smaller than the above-mentioned radius of curvature R is used, grinding work can be possible. Therefore, a cemented carbide (for example, a sintered metal including WC as a main component) capable of molding a high melting glass material under high pressure can be used as a material for the mold.

Furthermore, a method for working a mold for molding a lens according to the present invention includes grinding a lens molding surface of the mold for molding the lens by the use of a diamond grindstone. The lens molding surface is divided into at least three regions by concentric circles having an optical axis as a center, and among the three regions, a first region including the optical axis and a second region located at an outermost part being rotationally symmetric aspheric surfaces, and the third region which is sandwiched by the first region and the second region being a toric surface having the optical axis as an axis of rotation. A radius of the diamond grindstone used for the grinding work is the same as or smaller than the radius of curvature of the toric surface. According to the method for working a mold for molding a lens, since the method includes grinding work using a diamond grindstone, it is possible to produce a two-zone divided type mold for molding a lens which is made of a cemented carbide.

Furthermore, it is preferable in the method for working a mold for molding a lens of the present invention that the radius R of the diamond grindstone satisfies the following relationship (19).

$$0. \quad 7 \text{ mm} < R < 2. \quad 5 \text{ mm} \quad (1 \ 9)$$

When R is 0.7 mm or less, the diameter of a grindstone is too thin, and the accuracy of the worked surface becomes bad. On the other hand, when R is 2.5 mm or more, the toric surface region (connecting region) is broadened, and the aberration of the molded lens is deviated greatly from the design value.

Furthermore, it is preferable in the method for working a mold for molding a lens of the present invention that the radius R of the diamond grindstone satisfies the following relationship (20):

$$1. \quad 6 \text{ mm} < R < 2. \quad 1 \text{ mm} \quad (2 \ 0)$$

When the radius R of the grindstone is within this range, it is possible to reduce the width of the toric surface region and at the same time to maintain the diameter of the grindstone so as to have a sufficient intensity.

Furthermore, a configuration of a profile measuring device according

to the present invention includes a precision stage, a controller for controlling the precision stage, a length measuring means, a means for inputting design profile data, and a means for outputting a difference between the design profile data and measured data; wherein as the design profile data, a first rotationally symmetric aspheric surface is used in the region where the distant from the optical axis is less than the radius h_1 , a second rotationally symmetric aspheric surface is used in the region where the distance from the optical axis is not less than the radius h_2 , and a toric surface having the optical axis as a rotationally symmetric axis is used in the region between the radius h_1 and the radius h_2 . According to the configuration of the profile measuring device, it is possible to express one surface profile by using three surfaces including an inner aspheric surface, an outer aspheric surface and a toric surface having the optical axis of the middle region between the inner aspheric surface and outer aspheric surface as an axis of rotation. Therefore, the profile measuring device of the present invention has various advantages over the conventional profile evaluating device. In other words, when the fitting of the surface profile is carried out by the use of a higher order multinomial expression, fitting error surely occurs. In particular, when there is a portion having a difference in level, the fitting results are varied around the portion of the difference in level and the error becomes larger, and thus the measuring accuracy is deteriorated. However, according to the configuration of the profile measuring device of the present invention, it is possible to measure the profile faithfully based on the design profile, and thus the measuring accuracy can be improved greatly.

Brief Description of the Drawings

Fig. 1 is a view showing an optical path when light beams are focused onto an optical disk by using an objective lens for an optical disk according to a first embodiment of the present invention. Fig. 2 is a view showing a configuration of a surface profile at the side of the optical disk of the objective lens for an optical disk according to the first embodiment of the present invention. Fig. 3 is a graph showing an aberration in the objective lens for the optical disk of Example 1 according to the first embodiment of the present invention. Fig. 4 is a graph showing an intensity distribution of a point image of the objective lens for the optical disk of Example 1 according to the first embodiment of the present invention. Fig. 5 is a graph showing an aberration of the objective lens for an optical disk of Example 2 according to

the first embodiment of the present invention. Fig. 6 is a graph showing an intensity distribution of the point image of the objective lens for the optical disk of Example 2 according to the first embodiment of the present invention. Fig. 7 is a graph showing an aberration of the objective lens for an optical disk of Example 3 according to the first embodiment of the present invention. Fig. 8 is a graph showing an intensity distribution of the point image of the objective lens for an optical disk of Example 3 of the first embodiment of the present invention. Fig. 9 is a graph showing an aberration of the objective lens for an optical disk of Example 4 according to the first embodiment of the present invention. Fig. 10 is a graph showing an intensity distribution of point image of the objective lens for an optical disk of Example 4 according to the first embodiment of the present invention. Fig. 11 is a view showing an optical path when light beams are focused onto an optical disk by using an objective lens for an optical disk according to a second embodiment of the present invention. Fig. 12 is a view showing a configuration of a surface profile at the side of the optical disk of the objective lens for an optical disk according to the second embodiment of the present invention. Fig. 13 is a graph showing an aberration in the objective lens for the optical disk of Example 5 according to the second embodiment of the present invention. Fig. 14 is a graph showing an intensity distribution of a point image of the objective lens for the optical disk of Example 5 according to the second embodiment of the present invention. Fig. 15 is a view showing an optical path when light beams are focused onto an optical disk by using an objective lens for an optical disk according to a third embodiment of the present invention. Fig. 16 is a view showing a configuration of a surface profile at the side of the optical disk of the objective lens for an optical disk according to the third embodiment of the present invention. Fig. 17 is a graph showing an aberration in the objective lens for the optical disk of Example 6 according to the third embodiment of the present invention. Fig. 18 is a graph showing an intensity distribution of a point image of the objective lens for the optical disk of Example 6 according to the third embodiment of the present invention. Fig. 19 is a view showing a configuration of an optical head device and optical information recording and reproducing apparatus according to the fourth embodiment of the present invention. Fig. 20 is a view showing an optical path when light beams are focused onto an optical disk by using an objective lens for an optical disk according to a fifth embodiment of the present invention. Fig. 21 is a cross-sectional enlarged view in the direction of the

radius, showing a portion (portion A) in the vicinity of a toric surface region 106 shown in Fig. 20. Fig. 22 is a cross-sectional enlarged view in the direction of the radius, showing a portion in the vicinity of a toric surface region of one example of the objective lens obtained by actually calculating the lens profile according to the fifth embodiment of the present invention. Fig. 23 are graphs showing an aberration when data of DVD and CD are reproduced by using the objective lens according to the fifth embodiment of the present invention. Fig. 24 is a cross-sectional view in the direction of the radius, showing a mold for molding lens according to a sixth embodiment of the present invention. Fig. 25 is a schematic view showing a working method for the mold according to a seventh embodiment of the present invention. Fig. 26 is a view showing a configuration of a profile measuring device according to an eighth embodiment of the present invention. Fig. 27 is a view showing a configuration of an optical head device according to a ninth embodiment of the present invention. Fig. 28 is a view showing an optical path when light beams are focused onto an optical disk by using an objective lens for an optical disk according to a prior art.

Best Mode for Carrying Out the Invention

Hereinafter, the present invention will be described by way of the following embodiments.
[First Embodiment]

Fig. 1 is a view showing an optical path when light beams are focused onto an optical disk by using an objective lens for an optical disk according to a first embodiment of the present invention.

As shown in Fig. 1, the objective lens 2 of this embodiment includes a single lens having an aspheric surface on both sides. The surface 3 at the side of the light source of the objective lens 2 is a rotationally symmetric aspheric surface. Furthermore, the surface at the side of the optical disk 6 of the objective lens 2 includes an inner circumference region 4 and an outer circumference region 5. After incident light beams 1 enter the objective lens 2, they are focused onto an information medium surface 6a of the optical disk 6 via the objective lens 2.

As the optical disk 6 to be reproduced or recorded, a first optical disk made of a base material having a thickness of 0.6 mm and a second optical disk made of a base material having a thickness of 1.2 mm are prepared.

It is desirable that the wavefront aberration TW (unit: $m \lambda$: rms)

satisfies the following relationship (2) when light beams are focused through the first optical disk substrate.

$$0.05 < TW < 0.12 \quad (2)$$

When TW is 0.05 or less, the aberration in a desired aperture becomes too bad at the time of reproducing the second optical disk, so that a sufficient focusing property cannot be obtained. On the other hand, when TW is 0.12 or more, the aberration at the first optical disk becomes too bad. Also in this case, a sufficient focusing property cannot be obtained.

Furthermore, it is desirable that NA1 satisfies the following relationship (3).

$$0.38 < NA1 < 0.46 \quad (3)$$

wherein NA1 denotes a NA of the objective lens 6 at the aperture of the inner circumference region 4.

When NA1 is 0.38 or less, the aperture becomes too small at the time of reproducing the second optical disk, so that the spot diameter becomes too large. On the other hand, when NA1 is 0.46 or more, unless the aberration at the first optical disk exceeds the upper limit of the relationship (2), it is impossible to satisfy the aberration at the second optical disk. As a result, the aberration at the first optical disk is deteriorated.

Furthermore, it is desirable that $p(n-1)/\lambda$ satisfies the following relationship (4).

$$0.1 < p(n-1)/\lambda < 0.6 \quad (4)$$

wherein n denotes a refractive index of the objective lens 2 at the wavelength of the light source when the first optical disk is reproduced, p denotes a difference in level in the direction of the optical axis between the inner circumference region 4 and the outer circumference region 5, and λ denotes a wave length of the light source when the first optical disk is reproduced.

When $p(n-1)/\lambda$ is 0.1 or less or 0.6 or more, the light focusing property, in particular the peak intensity of the Airy ring when the first optical disk is reproduced, is increased excessively, and thus, the reproducing characteristics of the optical disk 6 is deteriorated.

Furthermore, it is desirable that a fifth order spherical aberration component S5 (unit is λ : rms) satisfies the following relationship (5), when light beams are focused through the first optical disk substrate.

$$-0.03 < S5 < 0.03 \quad (5)$$

When S5 is -0.03 or less, or 0.03 or more, the focusing property, in particular the peak intensity of the Airy ring when the first optical disk is

reproduced, is increased excessively, similar to the above-mentioned relationship (4). Thus, the reproducing characteristics of the optical disk 6 is deteriorated.

Furthermore, it is desirable that the thickness t_3 of the optical disk 6 satisfies the following relationship (6), when the aspheric profile of the inner circumference region 4 is optimized so that the spherical aberration is corrected with respect to the thickness t_3 of the optical disk 6.

$$0.8 < t_3 < 1.2 \quad (6)$$

When t_3 is 0.8 or less, the correction of the aberration with respect to the second optical disk is deficient. On the other hand, when t_3 is 1.2 or more, the aberration with respect to the first optical disk is deteriorated.

Fig. 2 is a view showing a configuration of a surface profile at the side of the optical disk of the objective lens for an optical disk according to the first embodiment of the present invention. As shown in Fig. 2, on the surface at the side of the optical disk 6 (see Fig. 1) of the objective lens 2, surfaces 7 that form the difference in level are provided in parallel to the optical axis (in the direction of the optical axis) at the boundary between the inner circumference region 4 and the outer circumference region 5. Although the surfaces 7 forming the difference in level are emphasized as compared with the actual size in Fig. 2 for easy understanding, the actual difference in level is about $0.3 \mu\text{m}$. Such a profile is ideal. However, for example, when the objective lens 2 is made by glass molding, the mold is made of a very hard material such as cemented carbide, and it is necessary to perform grinding work with a grindstone. Therefore, the portion having the difference in level between the inner circumference region 4 and the outer circumference region 5 becomes a circular arc profile as shown by reference numeral 8. However, the region in which the actual profile 8 is different from the ideal profile is at most $35 \mu\text{m}$ in the direction of the radius when, for example, the radius of the grindstone is 2 mm. This value is sufficiently small with respect to the whole effective diameter of the lens (about 4 mm), and thus the lens performance is hardly affected.

Next, the following are specific examples of numerical values of the objective lens 2 for an optical disk in this embodiment. In the below mentioned Examples, the remarks shown below are in common. Herein, a first surface of the objective lens 2 is a surface at the side of the light source, and a second surface is a surface at the side of the optical disk 6. Furthermore, the optical disk 6 is a parallel plate. Moreover, the wavelength

of a first light source to be focused onto the first optical disk was set to be 655 nm, and the wavelength of the second light source to be focused onto the second optical disk was set to be 800 nm. Furthermore, the refractive index of the first optical disk at the first light source was set to be 1.578353, and the refractive index of the second optical disk at the second light source was set to be 1.57153.

f 1 : a focal distance of the objective lens at the first light source

WD 1 : a working distance of the objective lens with respect to the first optical disk

n 1 : a refractive index of the objective lens at the first light source

d : a lens thickness of the objective lens

t 1 : a thickness of the first optical disk substrate

t 2 : a thickness of the second optical disk substrate

t 3 : a thickness of the optical disk substrate when an aspheric profile of

the inner circumference region is optimized so that the spherical aberration becomes 0

NA : NA of the objective lens

NA 1 : NA of the objective lens at the aperture of the inner circumference region

f 2 : a focal distance of the objective lens at the second light source

WD 2 : a working distance of the objective lens for the second optical disk

n 2 : a refractive index of the objective lens at the second light source

TW : wavefront aberration when light beams are focused onto the first optical disk from the first light source (unit is λ (wavelength): rms)

p : difference in level in the direction of the optical axis between the inner circumference region and the outer circumference region

S 3 : a third order spherical aberration component of the wavefront aberration when light beams are focused onto the first optical disk from the first light source (unit is λ (wavelength): rms)

S 5 : a fifth order spherical aberration component of the wavefront aberration when light beams are focused onto the first optical disk from the first light source (unit is λ (wavelength): rms)

Furthermore, the aspheric profile is expressed by the following relationship (21).

$$x = \frac{C_j h^2}{1 + \sqrt{1 - (1 + K_j) C_j^2 h^2}} + \sum A_{j,n} h^n \quad (21)$$

The remarks in the above-mentioned relationship (21) have the following denotations, respectively.

h : height from the optical axis

5 X : a distance between the point on the aspheric surface where the height from the optical axis is h and the tangential plane at the vertex of the aspheric surface

C_j : curvature at the vertex of the aspheric surface of a j -th surface of the objective lens ($C_j = 1/R_j$)

10 K_j : a conic constant of the j -th surface of the objective lens

$A_{j,n}$: the n -th order aspheric coefficient of the j -th surface of the objective lens

wherein j is 1 or 2.

15 Example 1

The following are specific numerical values of Example 1.

$$f_1 = 3.3142$$

$$WD_1 = 1.891$$

$$n_1 = 1.602892$$

20 $d = 1.8$

$$t_1 = 0.6$$

$$t_2 = 1.2$$

$$t_3 = 1.1$$

$$NA = 0.6$$

25 $NA_1 = 0.42$

$$f_2 = 3.3384$$

$$WD_2 = 1.521$$

$$n_2 = 1.59842$$

The following are the profile parameters of the first surface of the lens.

30 $R_1 = 2.1700$

$$K_1 = -6.72993 \times 10^{-1}$$

$$A_{1,4} = 2.08530 \times 10^{-3}$$

$$A_{1,6} = 7.99262 \times 10^{-5}$$

$$A_{1,8} = -7.79741 \times 10^{-7}$$

35 $A_{1,10} = -7.00341 \times 10^{-6}$

The following are the profile parameters at the inner circumference region of the second surface of the lens.

$$\begin{aligned}
R_2 &= -17.3537 \\
K_2 &= -3.61277 \times 10 \\
A_{2,4} &= 4.06605 \times 10^{-3} \\
A_{2,6} &= -1.06794 \times 10^{-3} \\
A_{2,8} &= 9.75688 \times 10^{-5} \\
A_{2,10} &= -2.01568 \times 10^{-6}
\end{aligned}$$

The following are the profile parameters at the outer circumference region of the second surface of the lens.

$$\begin{aligned}
R_2 &= -16.46001 \\
K_2 &= -7.90807 \times 10 \\
A_{2,4} &= 4.57207 \times 10^{-3} \\
A_{2,6} &= -1.35987 \times 10^{-3} \\
A_{2,8} &= 1.72647 \times 10^{-4} \\
A_{2,10} &= -8.80573 \times 10^{-6}
\end{aligned}$$

The following are the other parameters of the lens.

$$\begin{aligned}
TW &= 0.112 \\
p &= 0.00059274 \\
p(n-1)/\lambda &= 0.545 \\
S3 &= 0.0125 \\
S5 &= 0.0231
\end{aligned}$$

Fig. 3 is a graph showing aberrations according to this Example. Fig. 3(a) shows an optical path length aberration with respect to the first light source and the first optical disk, and Fig. 3(b) shows an optical path length aberration with respect to the second light source and the second optical disk. Furthermore, Fig. 4 is a graph showing a cross-sectional intensity distribution of a spot focused onto the first optical disk. Similarly, in the calculation of the cross-sectional intensity distribution of the other spots, it is assumed that the distribution of the quantity of incident light beams is uniform. A dashed line in Fig. 4 shows an ideal intensity distribution of a point image on the wavefront where the wavefront aberration is 0. Furthermore, the maximum peak of the calculated point image is normalized as 1. In Fig. 4, the intensity distribution of the point image around the Airy ring, which greatly affects the performance of the optical disk, is enlarged. The same is true in the below mentioned Examples 2 to 6.

The thickness of the first optical disk substrate is 0.6 mm. It is desirable that data of the first optical disk is reproduced by using the objective lens 2 having a NA of 0.6. As shown in Fig. 3(a), the optical path length

aberration with respect to the first light source and the first optical disk is about $\pm 0.25 \lambda$, and the wavefront aberration reaches 0.112λ : rms.

However, as is apparent from Fig. 4 showing the cross-sectional intensity of the spot, there is hardly any difference in the profile of the spot from the

profile of the ideal spot without aberration. Thus, it is possible to reproduce or record information without occurring any problems in performance of the optical disk 6.

Furthermore, it is desirable that data of the second optical disk is reproduced by using the objective lens 2 having a NA of about 0.45. However,

as shown in Fig. 3(b), the optical path length aberration with respect to the second light source and the second optical disk is extremely small in the range

wherein NA is not more than 0.42 and is rapidly increased in the range wherein NA is more than 0.42. When the light path length aberration is

extremely large, the light beams reflected from the information medium

surface of the optical disk 6 does not return to a photodetector. Consequently,

the same effect is exhibited as if the objective lens 2 is provided with an

aperture, and it is possible to reproduce or record information excellently

without providing the objective lens 2 with a new aperture with respect to the optical disk 6 having a thickness of 1.2 mm.

Example 2

The following are specific numerical values of Example 2.

$$f_1 = 3.3142$$

$$WD_1 = 1.890$$

$$n_1 = 1.602892$$

$$d = 1.8$$

$$t_1 = 0.6$$

$$t_2 = 1.2$$

$$t_3 = 1.0$$

$$NA = 0.6$$

$$NA_1 = 0.42$$

$$f_2 = 3.3384$$

$$WD_2 = 1.540$$

$$n_2 = 1.59842$$

The profile parameter of the first surface of the lens, and the profile parameters at the inner circumference region and the outer circumference region of the second surface of the lens are the same as in Example 1.

The following are the other parameters of the lens.

$$TW = 0.0743$$

$$p = 0.00030266$$

$$p(n-1)/\lambda = 0.279$$

$$S3 = 0.0025$$

$$S5 = 0.011$$

Fig. 5 is a graph showing aberrations according to this Example. Fig. 5(a) shows an optical path length aberration with respect to the first light source and the first optical disk, and Fig. 5(b) shows an optical path length aberration with respect to the second light source and the second optical disk. Furthermore, Fig. 6 is a graph showing a cross-sectional intensity distribution the spot focused onto the first optical disk.

The thickness of the first optical disk substrate is 0.6 mm. It is desirable that data of the first optical disk is reproduced by using the objective lens 2 having a NA of 0.6. As shown in Fig. 5(a), the optical path length aberration with respect to the first light source and the first optical disk is about -0.4λ at maximum, and the wavefront aberration is 0.074λ rms. However, as is apparent from Fig. 6 showing the cross-sectional intensity distribution of the spot, there is hardly any difference in the profile of the spot from the profile of the ideal spot without aberration. Thus, it is possible to reproduce and record information without occurring any problems in performance of the optical disk 6.

Furthermore, it is desirable that data of the second optical disk is reproduced by using the objective lens 2 having a NA of about 0.45. However, as shown in Fig. 5(b), the optical path length aberration with respect to the second light source and the second optical disk is extremely small in the range wherein NA is not more than 0.42 and is rapidly increased in the range wherein NA is more than 0.42. Therefore, similarly to Example 1, the same effect is exhibited as if the objective lens 2 is provided with an aperture, and it is also possible to reproduce or record information excellently without providing the objective lens 2 with a new aperture with respect to the optical disk 6 having a thickness of 1.2 mm.

Example 3

The following are specific numerical values of Example 3.

$$f1 = 3.3128$$

$$WD1 = 1.890$$

5
 10
 15
 20
 25
 30
 35

```

n 1=1. 6 0 2 8 9 2
d=1. 8
t 1=0. 6
t 2=1. 2
t 3=1. 0
NA=0. 6
NA 1=0. 4 4
f 2=3. 3 3 7 0
WD 2=1. 5 4 1
n 2=1. 5 9 8 4 2

```

The following are the profile parameters of the first surface of the lens.

```

R1=2. 1 7 0 0
K1=6. 7 2 9 9 3 × 1 0-1
A1, 4=2. 0 8 5 3 0 × 1 0-3
A1, 6=7. 9 9 2 6 2 × 1 0-5
A1, 8=-7. 7 9 7 4 1 × 1 0-7
A1, 10=-7. 0 0 3 4 1 × 1 0-6

```

The following are the profile parameters at the inner circumference region of the second surface of the lens.

```

R2=-1 7. 2 6 2 6 6
K2=-4. 5 5 6 8 9 × 1 0
A2, 4=4. 1 3 4 8 6 × 1 0-3
A2, 6=-1. 1 1 9 4 9 × 1 0-3
A2, 8=1. 0 4 4 2 3 × 1 0-4
A2, 10=-5. 6 1 5 0 8 × 1 0-7

```

The following are the profile parameters at the outer circumference region of the second surface of the lens.

```

R2=-1 6. 4 6 0 0 1
K2=-7. 9 0 8 0 7 × 1 0
A2, 4=4. 5 7 2 0 7 × 1 0-3
A2, 6=-1. 3 5 9 8 7 × 1 0-3
A2, 8=1. 7 2 6 4 7 × 1 0-4
A2, 10=-8. 8 0 5 7 3 × 1 0-6

```

The followings are the other parameters of the lens.

```

TW=0. 0 7 2
p=0. 0 0 0 1 5 1 3 5
p (n 1-1) / λ=0. 1 3 9

```

$$S\ 3 = 0.0031$$

$$S\ 5 = -0.028$$

Fig. 7 is a graph showing aberrations of this Example. Fig. 7(a) shows an optical path length aberration with respect to the first light source and the first optical disk, and Fig. 7(b) shows an optical path length aberration with respect to the second light source and the second optical disk. Furthermore, Fig. 8 is a graph showing a cross-sectional intensity of the spot focused onto the first optical disk.

The thickness of the first optical disk substrate is 0.6 mm. It is desirable that data of the first optical disk is reproduced by using the objective lens 2 having a NA of 0.6. As shown in Fig. 7(a), the optical path length with respect to the first light source and the first optical disk is about -0.5λ at maximum, and the wavefront aberration is 0.072λ : rms. However, as is apparent from Fig. 8 showing the cross-sectional intensity distribution of the spot, there is hardly any difference in the profile of the spot from the profile of the ideal spot without aberration. Thus, it is possible to reproduce and record information without occurring any problems in performance of the optical disk 6.

Furthermore, it is desirable that data of the second optical disk is reproduced by using the objective lens 2 having a NA of about 0.45. However, as shown in Fig. 7(b), the optical path length aberration with respect to the second light source and the second optical disk is extremely small in the range wherein NA is not more than 0.44 and is rapidly increased in the range wherein NA is more than 0.44. Therefore, similarly to Example 1, the same effect is exhibited as if the objective lens 2 is provided with an aperture, and it is also possible to reproduce or record information excellently without providing the objective lens 2 with a new aperture with respect to the optical disk 6 having a thickness of 1.2 mm.

Example 4

The following are specific numerical values of Example 4.

$$f\ 1 = 3.3106$$

$$WD\ 1 = 1.889$$

$$n\ 1 = 1.602773$$

$$d = 1.805$$

$$t\ 1 = 0.6$$

$$t\ 2 = 1.2$$

$t_3 = 0.9$
 $NA = 0.6$
 $NA_1 = 0.44$
 $f_2 = 3.3341$
 $WD_2 = 1.538$
 $n_2 = 1.59842$

The following are the profile parameters of the first surface of the lens.

$R_1 = 2.1700$
 $K_1 = -6.72993 \times 10^{-1}$
 $A_{1,4} = 2.08530 \times 10^{-3}$
 $A_{1,6} = 7.99262 \times 10^{-5}$
 $A_{1,8} = -7.79741 \times 10^{-7}$
 $A_{1,10} = -7.00341 \times 10^{-6}$

The following are the profile parameters at the inner circumference region of the second surface of the lens.

$R_2 = -17.0574$
 $K_2 = -5.33838 \times 10$
 $A_{2,4} = 4.25485 \times 10^{-3}$
 $A_{2,6} = -1.18514 \times 10^{-3}$
 $A_{2,8} = 1.22997 \times 10^{-4}$
 $A_{2,10} = -3.46201 \times 10^{-6}$

The following are the profile parameters at the outer circumference region of the second surface of the lens.

$R_2 = -16.46575$
 $K_2 = 0.0$
 $A_{2,4} = 6.72727 \times 10^{-3}$
 $A_{2,6} = -1.61122 \times 10^{-3}$
 $A_{2,8} = 1.96560 \times 10^{-4}$
 $A_{2,10} = -9.90970 \times 10^{-6}$

The following are the other parameters of the lens.

$TW = 0.0589$
 $p = 0.00030266$
 $p(n_1 - 1) / \lambda = 0.274$
 $S_3 = 0.0018$
 $S_5 = -0.003$

Fig. 9 is a graph showing aberrations of this Example. Fig. 9(a) shows an optical path length aberration with respect to the first light source

and the first optical disk, and Fig. 9(b) shows an optical path length aberration with respect to the second light source and the second optical disk. Furthermore, Fig. 10 is a graph showing a cross-sectional intensity distribution of the spot focused onto the first optical disk.

5 The thickness of the first optical disk substrate is 0.6 mm. It is desirable that data of the first optical disk is reproduced by using the objective lens 2 having a NA of 0.6. As shown in Fig. 9(a), the optical path length aberration with respect to the first light source and the first optical disk is about -0.3λ at maximum, and the wavefront aberration is 0.059λ : rms. However, as is apparent from Fig. 10 showing the cross-sectional intensity distribution of the spot, there is hardly any difference in the profile of the spot from the profile of the ideal spot without aberration. Particularly, the peak intensity of the Airy ring is further lower than the ideal intensity distribution of the point image. Thus, it is possible to record and reproduce information without occurring any problems in performance of the optical disk 6.

15 Furthermore, it is desirable that data of the second optical disk is reproduced by using the objective lens 2 having a NA of about 0.45. However, as shown in Fig. 9(b), the optical path length aberration with respect to the second light source and the second optical disk is extremely small in the range wherein NA is not more than 0.44 and is rapidly increased in the range wherein NA is more than 0.44. Therefore, similarly to Example 1, the same effect is exhibited as if the objective lens 2 is provided with an aperture and it is also possible to reproduce or record information excellently without providing the objective lens 2 with a new aperture with respect to the optical disk 6 having a thickness of 1.2 mm.

[Second Embodiment]

Fig. 11 is a view showing an optical path when light beams are focused onto an optical disk by the use of an objective lens for an optical disk according to the second embodiment of the present invention.

As shown in Fig. 11, the objective lens 2 according to this embodiment includes a single lens having aspheric surfaces on both sides. The surface 3 at the side of the light source of the objective lens 2 is a rotationally symmetric aspheric surface. Furthermore, the surface at the side of the optical disk 6 of the objective lens 2 includes an inner circumference region 9, a middle region 10 and an outer circumference region 11. After incident light beams enter the objective lens 2, they are focused onto an information medium 6a of the

optical disk 6 by the objective lens 2.

Herein, it is desirable that NA2 and NA3 satisfy the following relationships (7) and (8):

$$0.35 < \text{NA}2 < 0.43 \quad (7)$$

$$0.03 < \text{NA}3 - \text{NA}2 < 0.1 \quad (8)$$

wherein NA2 denotes a NA of the objective lens 2 at the boundary between the inner circumference region 9 and the middle region 10, and NA3 denotes a NA of the objective lens 2 at the boundary between the middle region 10 and the outer circumference region 11.

When NA2 is 0.35 or less, or 0.43 or more, the desirable spot diameter with respect to the second optical disk cannot be obtained. Furthermore, when NA3 - NA2 is 0.03 or less, the width of the middle region 10 becomes too narrow. Thus, it is difficult to correct the aberration with respect to the second optical disk. On the contrary, when NA3 - NA2 is 0.1 or more, the width of the middle region 10 becomes too broad. Thus, the aberration with respect to the first optical disk is deteriorated.

Furthermore, it is desirable that t4 satisfy the following relationship (9) when the aspheric profile of the middle region 10 is optimized so that the spherical aberration is corrected with respect to the thickness t4 of the optical disk 6.

$$1.4 < t4 < 2.0 \quad (9)$$

When t4 is 1.4 or less, or 2.0 or more, the aberration with respect to the second optical disk is deteriorated.

Fig. 12 is a view showing a configuration of a surface profile at the side of the optical disk of the objective lens according to the second embodiment of the present invention. As shown in Fig. 12, on the surface at the side of the optical disk 6 of the objective lens 2 (see Fig. 11), surfaces 12 forming the difference in level are provided approximately parallel to optical axis at the boundary between the inner circumference region 9 and the middle region 10. Although, the surfaces 12 forming the difference in level are emphasized as compared with the actual size in Fig. 12 for easy understanding, the actual difference in level is about $0.3 \mu\text{m}$. Such a profile is ideal. However, for example, when grinding work is actually carried out by the use of a grindstone, the portion having the difference in level at the boundary between the inner circumference region 9 and the middle region 10 becomes a circular arc profile as shown by reference numeral 13. However, the region in which the actual profile 13 is different from the ideal profile is at

most 35 μ m in the direction of the radius when, for example, the radius of the grindstone is 2 mm. This value is sufficiently small with respect to the whole effective diameter of the lens (about 4 mm), and thus the lens performance is hardly affected. On the other hand, the profile of the middle region 10 is determined so that difference in level does not occur at the boundary between the middle region 10 and outer circumference region 11.

Next, the following are specific examples of numerical values of the objective lens 2 for an optical disk in this embodiment. Herein, besides the common remarks described in the first embodiment above, the below mentioned remarks are added.

NA 2 : NA of the objective lens at the boundary between the inner circumference region and the middle region.

NA 3 : NA of the objective lens at the boundary between the middle region and the outer circumference region

t 4 : a thickness of the optical disk substrate when an aspheric profile of the middle region is optimized so that the spherical aberration becomes 0

Example 5

The following are specific numerical values of Example 5.

$$f\ 1 = 3.300$$

$$WD\ 1 = 1.890$$

$$n\ 1 = 1.602972$$

$$d = 1.8$$

$$t\ 1 = 0.6$$

$$t\ 2 = 1.2$$

$$t\ 4 = 1.8$$

$$NA\ 2 = 0.39$$

$$NA\ 3 = 0.44$$

$$f\ 2 = 3.3241$$

$$WD\ 2 = 1.538$$

$$n\ 2 = 1.59842$$

The following are the profile parameters of the first surface of the lens.

$$R_1 = 2.1700$$

$$K_1 = -6.72993 \times 10^{-1}$$

$$A_{1,4} = 2.08530 \times 10^{-3}$$

$$A_{1,6} = 7.99262 \times 10^{-5}$$

$$A_{1,8} = -7.79741 \times 10^{-7}$$

$$A_{1,10} = -7.00341 \times 10^{-6}$$

The following are the profile parameters at the inner circumference region and outer circumference region of the second surface of the lens.

$$R_2 = -16.46001$$

$$K_2 = -7.90807 \times 10$$

$$A_{2,4} = 4.57207 \times 10^{-3}$$

$$A_{2,6} = -1.35987 \times 10^{-3}$$

$$A_{2,8} = 1.72647 \times 10^{-4}$$

$$A_{2,10} = -8.80573 \times 10^{-6}$$

The following are the profile parameters at the middle region of the second surface of the lens.

$$R_2 = -18.9318$$

$$K_2 = 1.65803 \times 10$$

$$A_{2,4} = 2.81973 \times 10^{-3}$$

$$A_{2,6} = -4.83241 \times 10^{-4}$$

$$A_{2,8} = -3.23374 \times 10^{-5}$$

$$A_{2,10} = 1.75251 \times 10^{-5}$$

Fig. 13 is a graph showing aberrations of this Example. Fig. 13(a) shows an optical path length aberration with respect to the first light source and the first optical disk, and Fig. 13(b) shows an optical path length aberration with respect to the second light source and the second optical disk. Furthermore, Fig. 14 is a graph showing a cross-sectional intensity distribution of the spot focused onto the first optical disk.

The thickness of the first optical disk substrate is 0.6 mm. It is desirable that data of the first optical disk is reproduced by using the objective lens 2 having a NA of 0.6. As shown in Fig. 13(a), the optical path length aberration with respect to the first light source and the first optical disk is about -0.5λ at the NA of about 0.4. However, as is apparent from Fig. 14 showing the cross-sectional intensity distribution of the spot, there is hardly any difference in the profile of the spot from the profile of the ideal spot without aberration. Thus, it is possible to reproduce or record information without any problems in performance of the optical disk 6.

Furthermore, it is desirable that data of the second optical disk is reproduced by using the objective lens 2 having a NA of about 0.45. However, as shown in Fig. 13(b), the optical path length aberration with respect to the second light source and the second optical disk is small in the range wherein NA is not more than 0.44 and is rapidly increased in the range wherein NA is

more than 0.44. When the optical path length aberration is extremely large, the light beams reflected from the information medium surface of the optical disk 6 does not return to the photodetector. Consequently, the same effect is exhibited as if the objective lens 2 is provided with an aperture, and it is also possible to reproduce or record information excellently without providing the objective lens 2 with a new aperture with respect to the optical disk 6 having a thickness of 1.2 mm.

[Third Embodiment]

Fig. 15 is a view showing an optical path when light beams are focused onto an optical disk by using an objective lens for an optical disk according to a third embodiment of the present invention.

As shown in Fig. 15, the objective lens 2 according to this embodiment includes a single lens having an aspheric surface on both sides. The surface 3 at the side of the light source of the objective lens 2 is a rotationally symmetric aspheric surface. Furthermore, the surface at the side of the optical disk 6 of the objective lens 2 includes an inner circumference region 14, a middle region 15 and an outer circumference region 16. After incident light beams 1 enter the objective lens 2, they are focused onto an information medium surface 6a of the optical disk 6 by the objective lens 2.

Herein, it is desirable that t_5 satisfy the following relationship (10) when the aspheric profile of the middle region 15 is optimized so that the spherical aberration is corrected with respect to the thickness t_5 of the optical disk 6.

$$1. \quad 0 < t_5 < 1.4 \quad (10)$$

When t_5 is 1.0 or less, or 1.4 or more, the spherical aberration with respect to the second optical disk is deteriorated at the aperture at the inner side from the boundary between the inner circumference region 14 and the outer circumference region 16.

It is desirable that NA2 and NA3 satisfy the following relationship (12) and (13).

$$0.35 < \text{NA}2 < 0.43 \quad (12)$$

$$0.03 < \text{NA}3 - \text{NA}2 < 0.1 \quad (13)$$

wherein NA2 denotes a NA of the objective lens at the boundary between the inner circumference region 14 and the middle region 15, and NA3 denotes a NA of the objective lens at the boundary between the middle region 15 and the outer circumference region 16.

When NA2 is 0.35 or less, or 0.43 or more, the desirable spot diameter with respect to the second optical disk cannot be obtained. Furthermore, when NA3—NA2 is 0.03 or less, the width of the middle region 15 becomes too narrow, so that it is difficult to correct the aberration with respect to the second optical disk. On the contrary, when NA3—NA2 is 0.1 or more, the width of the middle region 15 becomes too broad, so that the aberration with respect to the first optical disk is deteriorated.

Fig. 16 is a view showing a configuration of a surface profile at the side of the optical disk of the objective lens according to the third embodiment of the present invention. As shown in Fig. 16, on the surface at the side of the optical disk of the objective lens 2 (see Fig. 15), the inner circumference region 14 is connected to the middle region 15 without difference in level at the boundary therebetween. Furthermore, the profile of the outer circumference region 16 is equal to the profile 17 in which optical path length is deviated by one wavelength with respect to the inner circumference region 14. Furthermore, the boundary between the middle region 15 and the outer circumference region 16 is determined so that the difference in level does not occur at the boundary between the middle region 15 and the outer region 16.

As mentioned above, in the objective lens 2 of this embodiment, since the difference in level is not provided between each region of the inner circumference region, the middle region and the outer circumference region, the working becomes easy.

Example 6

The following are specific numerical values of Example 6.

f 1 = 3 . 3 0 0
 WD 1 = 1 . 8 9 0
 n 1 = 1 . 6 0 2 9 7 2
 d = 1 . 8
 t 1 = 0 . 6
 t 2 = 1 . 2
 t 4 = 1 . 2
 NA 2 = 0 . 3 9
 NA 3 = 0 . 4 6
 f 2 = 3 . 3 2 4 1
 WD 2 = 1 . 5 3 9
 n 2 = 1 . 5 9 8 4 2

The following are the profile parameters of the first surface of the lens.

$$R_1 = 2.1700$$

$$K_1 = -6.72993 \times 10^{-1}$$

$$A_{1,4} = 2.08530 \times 10^{-3}$$

$$A_{1,6} = 7.99262 \times 10^{-5}$$

$$A_{1,8} = -7.79741 \times 10^{-7}$$

$$A_{1,10} = -7.00341 \times 10^{-6}$$

The following are the profile parameters at the inner circumference region and outer circumference region of the second surface of the lens, wherein the intersection point between the profile of the outer circumference region and optical axis is shifted toward the first surface in parallel by 0.00109 as compared with the intersection point between the inner circumference region and the optical axis.

$$R_2 = -16.46001$$

$$K_2 = -7.90807 \times 10$$

$$A_{2,4} = 4.57207 \times 10^{-3}$$

$$A_{2,6} = -1.35987 \times 10^{-3}$$

$$A_{2,8} = 1.72647 \times 10^{-4}$$

$$A_{2,10} = -8.80573 \times 10^{-6}$$

The following are the profile parameters at the middle region of the second surface of the lens, wherein the intersection point between the profile of the middle region and optical axis is shifted toward the first surface in parallel by 0.0003419 as compared with the intersection point between the inner circumference region and the optical axis.

$$R_2 = -17.3870$$

$$K_2 = -2.71760 \times 10$$

$$A_{2,4} = 3.98819 \times 10^{-3}$$

$$A_{2,6} = -9.93390 \times 10^{-4}$$

$$A_{2,8} = 6.64032 \times 10^{-5}$$

$$A_{2,10} = 6.11772 \times 10^{-6}$$

Fig. 17 is a graph showing aberrations of this Example. Fig. 17(a) shows an optical path length aberration with respect to the first light source and the first optical disk. Fig. 17(b) shows an optical path length aberration with respect to the second light source and the second optical disk. Furthermore, Fig. 18 is a graph showing a cross-sectional intensity distribution of the spot focused onto the first optical disk. As shown in Fig. 17(a), the optical path length aberration with respect to the first light source and the first optical disk is shifted by one wavelength when NA is 0.46 or

more. As is apparent from Fig. 18 showing the cross-sectional intensity distribution of the spot, there is hardly any difference in the profile of the spot from the profile of the ideal spot without aberration. Thus, it is possible to reproduce or record information without occurring any problems in performance of the optical disk 6.

Furthermore, it is desirable that data of the second optical disk is reproduced by using the objective lens 2 having a NA of about 0.45. However, as shown in Fig. 17(b), the optical path length aberration with respect to the second light source and the second optical disk is small in the range wherein NA is not more than 0.46 and is rapidly increased in the range wherein NA is more than 0.46. When the optical path length aberration is extremely large, the light beams reflected from the information medium surface of the optical disk 6 does not return to the photodetector. Consequently, the same effect is exhibited as if the objective lens 2 is provided with an aperture, and it is possible to reproduce or record information excellently without providing the objective lens 2 with a new aperture with respect to the optical disk 6 having a thickness of 1.2 mm.

Furthermore, the profile of the middle region 15 is designed so that the focal position at which a wavefront aberration of the inner circumference region 14 is minimized and the focal position at which a wavelength aberration of the middle region 15 is minimized are the same when light beams are focused onto the second optical disk. Therefore, when the light beams reflected from the information medium surface of the optical disk 6 enter the photodetector, light beams return to the same portions with respect to the inner circumference region 14 and the middle region 15. As a result, the accurate signal light can be obtained.

Furthermore, in this Example, since the third order spherical aberration component of the wavefront aberration in the inner circumference region 14 and the middle region 15 is as small as 0.0019λ , it is possible to reproduce and record information of the second optical disk excellently.

It is desirable that the objective lens 2 shown in Examples 1 to 6 is formed by glass molding or plastic molding. This is because by working a mold of the aspheric profile, lenses having the same profile and the same performance can be mass-produced at low cost.

[Fourth Embodiment]

Next, an optical head device and an optical information recording and

reproducing apparatus using the objective lens for an optical disk according to one of the first to third embodiments will be described with reference to Fig.

19. Fig. 19 is a view showing a configuration of an optical head device and an optical information recording and reproducing apparatus according to the

fourth embodiment of the present invention.

As shown in Fig. 19, a light flux 19 emitted from a semiconductor laser 18 having a wavelength of 655 nm (that is the first light source) is made to be approximately parallel light by a collimate lens 20. The light flux 19 that has been made to be approximately parallel light by the collimate lens 20 passes through a beam splitter 21 and is focused onto the information medium surface 23a of the first optical disk 23 having a thickness of 0.6 mm by the optical lens 2 shown in any one of the first to third embodiments.

Furthermore, a light flux 25 emitted from a semiconductor laser 24 having a wavelength of 800 nm (that is a second light source) is made to be

approximately parallel light by a collimate lens 26. The light flux 25 that has been made to be approximately parallel light by the collimate lens 26 is reflected from the beam splitter 21 and is focused onto the information medium surface 27a of the second optical disk 27 having a thickness of 1.2 mm

by the same objective lens 2. Herein, the objective lens 2 is attached to a movable holder 28, which allows the focal point of the objective lens 2 to be matched to the information medium surface in accordance with blurring of the surface of the optical disk and serves as limiting the aperture of the objective lens 2. The light focusing spot is diffracted by a roughness part formed on the information medium surface 23a of the first optical disk 23 or on the

information medium surface 27a of the second optical disk 27. The laser beams (light flux 19 or 25) diffracted and reflected by the information medium surface 23a of the first optical disk 23 or the information medium 27a of the second optical disk 27 is reflected from the beam splitter 21 and refracted by a convex lens 29 and a cylindrical lens 30 and focused onto the photodetector 31.

Then, the quantity of light modulated at the information medium surface 23a of the first optical disk 23 or the information medium surface 27a of the second optical disk 27 is detected by an electric signal of the photodetector 31, and the data is read out.

As mentioned above, when light beams are focused onto the first optical disk 23 having a substrate thickness of 0.6 mm by the use of the first light source having a wavelength of 655 nm, although the objective lens 2 has a large wavefront aberration value itself, the intensity of the Airy ring of the

focused spot in relatively low. The intensity of the Airy ring affects the recording and reproducing of the first optical disk 23. Therefore, excellent recording and reproducing characteristics can be obtained.

As mentioned above, when light beams are focused onto the second
5 optical disk 27 having a substrate thickness of 1.2 mm by the use of the second light source having a wavelength of 800 nm, the aperture of the lens holder 28 still corresponds to NA of 0.6, when NA of the objective lens 2 is 0.4 or 0.45 or more, the optical path length aberration is rapidly increased. Thus, the same effect is exhibited as in a state in which the aperture is provided at the
10 objective lens 2. Furthermore, at the light receiving side, when NA is 0.4 or 0.45 or more, light beams are present outside the photodetector 31 because the optical path length aberration is large. Consequently, the same effect in which the objective lens 2 is masked (provided with an aperture) is exhibited. Needless to say, when NA is 0.4 or 0.45 or less, the optical path length
15 aberration is sufficiently corrected with respect to the second light source. Therefore, it is possible to obtain excellent recording and reproducing characteristics with respect to the second optical disk 27 having a thickness of 1.2 mm.

As mentioned above, by providing the objective lens 2 with the
20 aberration suitable to the respective optical disk, it is possible to carry out excellent recording and reproducing with respect to two different optical disks with the use of one lens.

In the above-mentioned embodiments, the wavelength of the light source is set to be 655 nm and 800 nm. However, other wavelengths, for
25 example, the combination of 400 nm and 650 nm etc. may be employed.

Furthermore, in the above-mentioned embodiments, the substrate thickness of the two kinds of optical disks are set to be 0.6 mm and 1.2 mm. However, other thicknesses, for example, the combination of 0.3 mm and 0.6
30 mm etc. may be employed.

Furthermore, in the above-mentioned embodiments, the refractive index of the objective lens 2 is set to be about 1.6. However, a material having a refractive index from 1.45 to 2.0 etc. may be used as long as the material is glass material or plastic material.

Furthermore, in the above-mentioned embodiments, NA for the first
35 optical disk is set to be 0.6. However, NA of 0.6 or more and NA of 0.6 or less may be employed.

Furthermore, in the above-mentioned embodiments, the difference in

level etc. is formed on the surface at the side of the optical disk (the second surface) of the objective lens 2. However, the difference in level etc. may be provided on the surface at the side of the light source (a first surface) of the objective lens 2. Furthermore, the function shown in the above mentioned
 5 embodiments may be added to an optical element, such as a parallel plate, etc. other than the conventional single lens.

Furthermore, in the above-mentioned embodiments, the aperture limitation is not varied in accordance with the substrate thickness of the optical disk with respect to the objective lens 2. However, aperture limitation
 10 may be added in accordance with the different substrate thickness.

Furthermore, in the above-mentioned embodiments, the case where approximately parallel light beams are incident into the objective lens 2 is described. However, light beams emitted from the semiconductor laser may be focused directly by one lens. Furthermore, instead of making
 15 approximately parallel light beams by a collimate lens, a lens having an finite magnifying power for making divergent light beams or convergent light beams may be used.

[Fifth Embodiment]

In the present invention, aspheric surface refers to a profile in which the spherical surface having a paraxial radius of curvature as a radius is provided with the deviation. In other words, aspheric surface is a profile that
 20 can be expressed by the following equation (22). Moreover, the lens profile capable of being expressed by the following equation (22) with the necessary and sufficient accuracy in optical design (profile error of less than 10 nm) may
 25 be designed by the use of the different equation.

$$z = \frac{(1/r)^2 h^2}{1 + \sqrt{1 - (1+k)(1/r)^2 h^2}} + \sum_j A_j h^j \quad (22)$$

30 The following are denotations of the variables used in the above-mentioned equation (22).

z: sag

h: height from the optical axis

r: radius of curvature

35 k: a conic constant

A_j: the j-th order aspheric coefficient

Fig. 20 is a view showing an optical path when light beams are focused

onto an optical disk by using an objective lens for an optical disk according to a fifth embodiment of the present invention.

As shown in Fig. 20, an objective lens 101 of this embodiment includes a single lens. Furthermore, the surface at the side of the optical disk 102 of the objective lens 101 includes a first aspheric surface region 104 at the inner circumference portion including the optical axis 107, a second aspheric surface region 105 at the outer circumference portion, and a toric surface region 106 sandwiched by the first aspheric surface region 104 and the second aspheric surface region 105 and having an optical axis 107 as a rotationally symmetric central axis. Incident light 103 from the light source is incident on the objective lens 101, and then focused onto the optical disk 102 by the objective lens 101.

The first and second aspheric surface regions 104 and 105 of the objective lens 101 are designed so that data on CD and DVD disks can be reproduced excellently with one lens. Specifically, the first aspheric surface region 104 including an optical axis 107 is designed so that it can excellently reproduce data on a CD by the use of a light source emitting light beams having a wavelength of 780 nm, and the second aspheric surface region 105 is designed so that it can excellently reproduce data on a DVD by the use of a light source emitting light beams having a wavelength of 660 nm. By connecting these first and second aspheric surface regions 104 and 105 with each other with a discontinuous portion having a difference in level mentioned below, it is possible to reproduce excellently data on a CD or DVD disks by the use of a light source having the respective wavelength over the entire region of the lens.

In Fig. 20, the surface having a large central radius of curvature is divided into three regions with the toric surface region 106 as a boundary. This is effective in enhancing the degree of freedom in selecting the diameter of the grindstone for working a mold. This will be described in detail in the next embodiment.

Fig. 21 is a cross-sectional enlarged view in the direction of radius showing a portion (portion A) in the vicinity of a toric surface region 106 shown in Fig. 20.

As shown in Fig. 21, the toric surface region 106 is a toric surface obtained by rotating a circular arc having a radius R with an optical axis 107 (see Fig. 20) as a center. This toric surface region 106 is formed so that it is in contact with the second aspheric surface region 105 of the outer

circumference portion and intersects the first aspheric surface region 104 of the inner circumference portion. Herein, that the toric surface region 106 “is in contact with” the second aspheric surface region 105 means that tilts of tangential at the connecting point of the surface curve of the toric surface region 106 and the surface curve of the second aspheric surface region 105 coincide with each other at the radial cross section. Furthermore, that the toric surface region 106 “intersects” the first aspheric surface region 104 means that tilts of the tangential lines at the connecting point of the surface curve of the toric surface region 106 and the surface curve of the first aspheric surface region 104 do not coincide with each other, and intersect at the predetermined angle.

Final design profile is shown by solid line in Fig. 21.

It is desirable that the width of the toric surface region 106 in the direction of the radius (width of the circular arc) w satisfies the following relationship (16).

$$0.02 \text{ mm} < w < 0.04 \text{ mm} \quad (16)$$

As shown in Fig. 21, the width w is defined as the difference between the height of the connecting point between the first aspheric surface region 104 and toric surface region 106 from the optical axis 107 and the height of the connecting point between the second aspheric surface region 105 and the toric surface region 106 from the optical axis 107. When w is 0.02 mm or less, the profile cannot be worked by a grindstone, thus making it difficult to produce the lens. On the other hand, when w is 0.04 mm or more, the difference between the actual lens profile and the ideal design profile is too large, and thus the lens performance is not sufficient.

Furthermore, it is desirable that the radius R of the circular arc forming the toric surface region 106 satisfies the following relationship (14).

$$0.7 \text{ mm} < R < 2.5 \text{ mm} \quad (14)$$

When R is 0.7 mm or less, a mold cannot be worked by grinding, thus making it difficult to produce the lens. On the other hand, when R is 2.5 mm or more, the width of the circular arc portion is too broad, thus deteriorating the lens performance.

Furthermore, it is desirable that the radius R of the circular arc forming the toric surface region 106 satisfies the following relationship (15).

$$1.6 \text{ mm} < R < 2.1 \text{ mm} \quad (15)$$

[Example 7]

Fig. 22 is a cross-sectional enlarged view in the direction of the radius, showing a portion in the vicinity of a toric surface region of one example of the objective lens obtained by actually calculating the lens profile according to the present invention. In Fig. 22, a horizontal axis shows a height h (mm) from the optical axis 107, and a vertical axis shows a sag amount z with the intersection of the first aspheric surface region 104 and the optical axis 107 as an origin.

The following Table 1 shows aspheric data at the first aspheric surface region 104 of the inner circumference portion.

[Table 1]

$$\begin{aligned} r &= -1.682 \times 10 \\ k &= -7.90807 \times 10 \\ A_3 &= 2.605947654 \times 10^{-3} \\ A_4 &= 1.054073967 \times 10^{-4} \\ A_6 &= 6.605216379 \times 10^{-4} \\ A_8 &= -4.966151680 \times 10^{-4} \\ A_{10} &= 8.362178008 \times 10^{-5} \end{aligned}$$

The following Table 2 shows aspheric data at the second aspheric surface region 105 of the inner circumference portion.

[Table 2]

$$\begin{aligned} r &= -1.682 \times 10 \\ k &= -4.10782 \times 10 \\ A_3 &= -2.083119392 \times 10^{-3} \\ A_4 &= 7.583760761 \times 10^{-3} \\ A_6 &= -2.145398325 \times 10^{-2} \\ A_8 &= 3.23346325 \times 10^{-4} \\ A_{10} &= -2.125916694 \times 10^{-5} \end{aligned}$$

In Fig. 22, when an aspheric surface curve of the first aspheric surface region 104 and an aspheric surface curve of the second aspheric surface region 105 are extended, respectively, toward each other as shown by the dashed lines, distance D in the direction of the optical axis of both curves at the point where the height h from the optical axis 107 is 1.07 mm is 0.303 μ m. In the present invention, such a distance in the direction of the optical axis at the connecting portion of the first aspheric surface region and the second aspheric

surface region is called “a difference in level at the connecting portion.”

Furthermore, connecting of the first aspheric surface region and the second aspheric surface region in the direction of the optical axis with the predetermined direction (i.e., a difference in level) is referred to as “connecting with a difference in level.” The radius R of the circular arc forming the toric surface region 106 is 2 mm, a coordinate of the central point of the circular arc is (h, z)=(1.006469, -2.026898). Furthermore, the width w of the toric surface region 106 connecting the aspheric surface regions 104 and 105 of the inner and outer circumferences is about $34\text{ }\mu\text{m}$.

Fig. 23 shows aberration curves (optical path length difference curve: OPD) when data on a DVD and CD are reproduced. Fig. 23(a) shows an aberration curve when data on a DVD is reproduced, and Fig. 23(b) shows an aberration curve when data on a CD is reproduced.

Herein a curve shown by a broken line shows an aberration curve under the ideal condition in which aspheric surface regions 104 and 105 of the inner and outer circumferences are not connected by the toric surface region 106 as in this embodiment, but connected with the difference in level as shown by the dashed lines of Fig. 22. In the objective lens of this embodiment shown by the solid line of Fig. 22, as compared with the objective lens under the ideal condition, the aberration curve is deformed in the toric surface region 106, however, this does not affect the reproduction on DVD and CD disks.

[Sixth Embodiment]

Fig. 24 is a cross-sectional view in the direction of radius showing a mold for molding a lens according to a sixth embodiment of the present invention. As shown in Fig. 24, a lens surface of the mold 501 of this embodiment is divided into three regions by concentric circles having a rotationally symmetric central axis as a center. Specifically, the molding surface of the mold 501 of this embodiment is divided into a first aspheric surface region 504 including a rotationally symmetric central axis, a third aspheric surface region 505 located at an outermost part and a toric surface region 506 having a rotationally symmetric central axis as a center of rotation and sandwiched between the first aspheric region 504 and the third aspheric surface region 505. It is desirable that the radius of curvature R of the toric surface region 506 at a cross-section in the direction of the radius satisfies the following relationship (17).

$$0.7 \text{ mm} < R < 2.5 \text{ mm} \quad (17)$$

It is further desirable that the radius of curvature R of the toric surface region 506 at a cross-section in the direction of the radius satisfies the following relationship (18).

$$1.6 \text{ mm} < R < 2.1 \text{ mm} \quad (18)$$

If a grindstone having a radius that is the same as or smaller than the above-mentioned radius of curvature R is used, a grinding work is possible. Therefore, a cemented carbide (for example, a sintered metal including WC as a main component) capable of molding a high melting temperature glass material under high pressure can be used as a material for the mold 501.

The profile of the worked mold 501 is measured by a profile measuring device. When a stylus type measuring device is used, the tip profile of the stylus (probe) is required to have a radius of curvature smaller than the minimum radius of curvature of the profile to be measured. Namely, when the profile to be measured has a curve profile smaller than the tip diameter of the probe, the part of the measurement result is deviated, and consequently it is impossible to measure accurately. Using a probe having a small diameter is one solution to prevent this. However, the roundness of the small diameter probe is not so good. In particular, the measuring accuracy at the inclined face is deteriorated. With the mold 501 having a toric surface region 506 with a radius of curvature R being in the above-mentioned range, it is possible to accurately measure the profile by the use of the probe having a tip radius of curvature of about $500 \mu\text{m}$.

Furthermore, when an optical measuring device is used, as compared with the case where the aspheric surface regions 104 and 105 of the inner and outer circumferences are connected with the difference in level as shown by the dashed lines in Fig. 22, the change in the profile of the toric surface region 506 is sufficiently smooth in the wavelength order, so that the wave face of the measured light is connected continuously. Therefore, also in this case, precise measurement is possible.

[Seventh Embodiment]

As a material for a mold for molding glass material, a high hardness material (cemented carbide) excellent in heat resistance so that it is not deformed even if it is pressed at a temperature higher than the melting point of glass is used. Working of cemented carbide is carried out by grinding work with the use of the diamond grindstone.

Fig. 25 is a schematic view showing a working method for the mold according to a seventh embodiment of the present invention. Fig. 25(a) is a front elevational view and Fig. 25(b) is a side elevational view.

As shown in Fig. 25, a mold 601 to be worked is rotated about a rotation axis 602 of the mold 601. A grindstone 603 is rotated about a rotation axis of the grindstone 603. The grindstone 603 moves along a curve 605 that is offset from the profile of the worked surface by the radius R of the grindstone 603 so as to work the surface of the mold into the lens profile 606.

By setting the radius R of the grindstone 603 to be the same as or smaller than the radius of curvature of the toric surface region to be worked, it is possible to work the mold described in the sixth embodiment. When the radius R of the grindstone 603 is 80% or more, preferably 90% or more, more preferably 95% or more, of the radius of curvature of the toric surface region to be worked, it is possible to work the mold efficiently.

As is apparent from Fig. 25(b), the diameter of the axle 607 (an axle diameter) of the grindstone 603 is limited by the sag of the lens to be worked, diameter R of the grindstone 603, and a clearance between the mold 601 to be worked and the axle 607 of the grindstone 603. When the radius R of the grindstone 603 is small or the sag of the lens to be worked is large, it is necessary to make the axle 607 of the grindstone 603 thin. When the axle 607 of the grindstone 603 is made thin, a bending, etc. occurs, which may lead the deterioration of working accuracy. In order to secure a sufficient axle diameter, it is necessary to carry out a working of the difference in level on the surface having a small amount of sag and to increase the radius R of the grindstone 603 sufficiently as compared with the sag of the lens.

In order to work a mold for molding a zone divided type lens excellently, it is desirable that the radius R of the grindstone 603 satisfies the following relationship (19):

$$0.7 \text{ mm} < R < 2.5 \text{ mm} \quad (19)$$

When R is 0.7 mm or less, since the axle diameter of the grindstone 603 is too thin, the accuracy of the worked surface becomes bad. On the other hand, when R is 2.5 mm or more, the toric surface region (connecting region) is broadened, and the aberration of the molded lens is deviated greatly from the design value. Furthermore, it is further desirable that the radius R of the grindstone 603 satisfies the following relationship (20).

$$1.6 \text{ mm} < R < 2.1 \text{ mm} \quad (20)$$

When the radius R of the grindstone 603 is within this range, it is

possible to reduce the width of the toric surface region and at the same time to maintain the axle diameter of the grindstone 603 so as to have a sufficient strength excellently.

5 [Eighth Embodiment]

Fig. 26 is a view showing a configuration of a profile measuring device according to an eighth embodiment of the present invention.

As shown in Fig. 26, a test mold 701 is placed on a stage 702. The stage 702 is movable in the horizontal direction by a stage controller 703. A
10 stylus 704 is controlled/maintained by a stylus controller 705 so that it is movable in a vertical direction while being in contact with the surface of the test mold 701.

The stage controller 703 and the stylus controller 705 transmit the horizontal coordinate Y of the stage 702 and its corresponding vertical
15 coordinate Z of the stylus 704 to an arithmetic unit 706. Coordinate data rows consisting of Y and Z serves as the profile data (measuring data) information of the test mold 701. Design profile data of the test mold 701 is stored in a hard disk drive (HDD) 707. The arithmetic unit 706 displays a working error obtained by comparing the measurement data with design
20 profile data on a display 708. Furthermore, a keyboard 709 is used for a data input or an operation of the profile measuring device.

In the profile measuring device of the present invention, it is possible to use the rotationally symmetric aspheric surfaces of the inner and outer circumferences and its connecting surface, that is, a toric surface having a
25 light axis as a axis of rotation as the design profile data. Therefore, it is possible to measure the profile of the worked lens profile without error.

Specifically, in a case where the mold profile for a single lens described in the fifth embodiment, the height h_1 from the optical axis of the boundary portion between a first aspheric surface region of the inner circumference portion and a toric surface region is 1.06, and the height h_2 from the optical axis the the boundary portion between a second aspheric region of the outer circumference portion and a toric surface region is 1.094. Therefore, the profile is expressed by using the coefficients shown in Table 1 into the above-mentioned equation (22) in the range of $0 < h < 1.06$, and by using the
30 coefficients shown in Table 2 into the below-mentioned equation (23) in the range of $1.094 < h$.

$$z = \frac{(1/r)^2 h^2}{1 + \sqrt{1 - (1+k)(1/r)^2 h^2}} + A_0 + \sum_j A_j h^j \quad (23)$$

In the above-mentioned equation (23), A_0 is a coefficient for running the second aspheric surface region of the outer circumference portion in parallel in the direction of the z-axis so that the difference in level becomes appropriate. In this case, this coefficient becomes 0.303. Furthermore, in the range of $1.06 < h < 1.094$, the profile is expressed by an equation of a circular arc having a center coordinate $(h, z) = (1.006469, -2.026898)$ and a radius of 2 mm. At this time, the profile of the circular arc is expressed by the following equation (24).

$$z = z_0 + \sqrt{R^2 - (h - h_0)^2} \quad (24)$$

wherein $h_0 = 1.006469$, and $z_0 = -2.026898$.

In this embodiment, the case where the stylus type profile measuring device is used is described. However, the profile measuring device is not necessarily limited to this type of device. Even if an optical non-contact type profile measuring device or a measuring device using interatomic force is used, the same effect can be obtained.

[Ninth Embodiment]

Fig. 27 is a view showing a configuration of an optical head device according to a ninth embodiment of the present invention.

In Fig. 27, numerals 801 and 802 denote laser modules for DVD and CD devices, respectively. The laser module 801 for the DVD device includes a semiconductor laser for emitting laser beams having a wavelength of 660 nm and a photodetector for receiving reflected light beams from a disk (DVD 806). Similarly, the laser module 802 for the CD device includes a semiconductor laser for emitting laser beams having a wavelength of 780 nm and a photodetector for receiving reflected light beams from a disk (CD 807).

When the data on the DVD is reproduced, a light flux emitted from the laser module 801 for the DVD device passes through a beam splitter 803, is converted into an approximately parallel light flux by a collimate lens 804 and then enters an objective lens 805 of the present invention. The objective lens

805 of the present invention forms a focused spot on the information recording surface of a DVD 806. The reflected light beams from DVD 806 are converted into parallel light beams by the objective lens 805, and converted into convergent light beams by the collimate lens 804. The convergent light beam passes through the beam splitter 803, and is then focused onto the photodetector of the laser module 801 for the DVD device.

Next, the operation when data on the CD is reproduced will be described. The light beams from the laser module 802 for the CD device are reflected from the beam splitter 803, and then converted into an approximately parallel light flux by the collimate lens 804, and then enters the objective lens 805 of the present invention. The objective lens 805 of the present invention forms a focused spot on the information recording surface of CD 807. The reflected light beams from the CD 807 are converted into an approximately parallel light flux by the collimate lens 804, then reflected from the beam splitter 803, and focused onto the photodetector of the laser module 802 for the CD device.

Herein, since a single glass lens of the present invention is used as the objective lens 805, the fluctuation of the aberration of the objective lens 805 due to changes in temperature is sufficiently small. Therefore, when it is necessary to secure the operation over a wide temperature range, for example, as a vehicle apparatus, etc. an excellent performance can be exhibited.

In the above-mentioned fifth to ninth embodiments, as the objective lens having a DVD/CD compatibility, the single lens divided into two zones including the inner aspheric surface region and the outer aspheric surface region is described. However, even if the design in which a three-zone divided type single lens is used, by connecting the difference in level portion of each zone on the toric surface having an optical axis as a rotationally symmetric axis, the same effect can be obtained.

Industrial Applicability

As mentioned above, according to the present invention, it is possible to attain an objective lens for an optical disk that is capable of focusing a point image through the first and second optical disk substrates each having a different thickness. The objective lens is applicable for an optical head device that reads data on CD or CD-ROM disks having a disk thickness of 1.2 mm and data on DVD or DVD-ROM disks having a disk thickness of 0.6 mm using one optical head.

CLAIMS

1. An objective lens for an optical disk comprising a single lens having aspheric surfaces on both sides and focusing light beams into a point image through first and second optical disk substrates each having a different thickness,

at least one of the aspheric surfaces comprising two regions including an inner circumference region at an inner side of a circular aperture having an optical axis as a center and an outer circumference region located at an outer side with respect to the inner circumference region, the aspheric profile of the outer circumference region correcting a spherical aberration with respect to the first optical disk substrate which has a smaller thickness than the second optical disk substrate, and the aspheric profile of the inner circumference region correcting a spherical aberration with respect to the second optical disk substrate, the outer circumference region and the inner circumference region are in contact with each other at the boundary therebetween with a difference in level in the direction of the optical axis,

wherein the objective lens satisfies the following relationships (1) to (4);

$$t_1 < t_2 \quad (1)$$

$$0.05 < TW < 0.12 \quad (2)$$

$$0.38 < NA_1 < 0.46 \quad (3)$$

$$0.1 < p(n-1)/\lambda < 0.6 \quad (4)$$

wherein t_1 denotes a thickness of the first optical disk substrate, t_2 denotes a thickness of the second optical disk substrate, NA_1 denotes a NA of the objective lens at the aperture of the inner circumference region, TW denotes a wavefront aberration when light beams are focused through the first optical disk substrate (unit is λ : rms), n denotes a refractive index of the objective lens at the wavelength of a light source when data of the first optical disk is reproduced, p denotes a difference in level between the inner circumference region and the outer circumference region in the direction of the optical axis; and λ denotes a wavelength of the light source when data of the first optical disk is reproduced.

2. The objective lens for an optical disk according to claim 1, wherein the third order spherical aberration component S_3 of the wavefront aberration is approximately 0 when light beams are focused through the first optical disk substrate.

3. The objective lens for an optical disk according to claim 1, wherein a fifth order spherical aberration component S_5 (unit is λ : rms) of the wavefront aberration satisfies the following relationship (5) when light beams are focused through the first optical disk substrate.

$$-0.03 < S_5 < 0.03 \quad (5)$$

4. The objective lens for an optical disk according to claim 1, wherein the thickness t_3 of the optical disk substrate satisfies the following relationship (6), when the aspheric profile of the inner circumference region is optimized so that the spherical aberration is corrected with respect to the thickness t_3 of the optical disk substrate.

$$0.8 < t_3 < 1.2 \quad (6)$$

5. The objective lens for an optical disk according to claim 1, wherein the cross section of the portion having the difference in level between the inner circumference region and the outer circumference region has a circular arc profile.

6. The objective lens for an optical disk according to claim 1, which is formed by glass molding or plastic molding.

7. An objective lens for an optical disk comprising a single lens having aspheric surfaces on both sides and focusing light beams into a point image through first and second optical disk substrates each having a different thickness,

at least one of the aspheric surfaces comprising three regions including of an inner circumference region at an inner side of a circular aperture having an optical axis as a center, a middle region located at an outer side with respect to the inner circumference region and surrounded by another circular aperture that is located at an outer side of the circular aperture, and an outer circumference region located at an outer side with respect to the middle region, the aspheric profiles of the inner circumference region and the outer circumference region correcting a spherical aberration with respect to the first optical disk substrate which has a smaller thickness among the first and second optical disk substrates, and the aspheric profile of the middle region correcting a spherical aberration with respect to an optical disk substrate

having a thickness that is larger than any of the first and second optical disk substrates, wherein the objective lens satisfies the following relationships (7) and (8);

$$0.35 < NA_2 < 0.43 \quad (7)$$

$$0.03 < NA_3 - NA_2 < 0.1 \quad (8)$$

wherein NA_2 denotes a NA of the objective lens at the boundary between the inner circumference region and the middle region, and NA_3 denotes a NA of the objective lens at the boundary between the middle region and the outer circumference region.

8. The objective lens for an optical disk according to claim 7, wherein the thickness t_4 of the optical disk substrate satisfies the following relationship (9), when the aspheric profile of the middle region is optimized so that the spherical aberration is corrected with respect to the thickness t_4 of the optical disk substrate.

$$1.4 < t_4 < 2.0 \quad (9)$$

9. The objective lens for an optical disk according to claim 7, wherein either the boundary in which the inner circumference region is connected to the middle region or the boundary in which the middle region is connected to the outer circumference region does not have a difference in level.

10. The objective lens for an optical disk according to claim 7, wherein the cross section of the portion having a difference in level between the inner circumference region and the middle region or the cross section of the portion having a difference in level between the middle region and the outer circumference region has a circular arc profile.

11. The objective lens for an optical disk according to claim 7, which is formed by glass molding or plastic molding.

12. An objective lens for an optical disk comprising a single lens having aspheric surface on both sides and focusing light beams into a point image through first and second optical disk substrates each having a different thickness,

at least one of the aspheric surfaces comprising three regions including of an inner circumference region at an inner side of a circular aperture having

an optical axis as a center, a middle region located at an outer side with respect to the inner circumference region and surrounded by another circular aperture that is located at an outer side of the circular aperture, and an outer circumference region located at an outer side with respect to the middle region, the aspheric profiles of the inner circumference region and the outer circumference region correcting a spherical aberration with respect to the first optical disk substrate which has a smaller thickness than the second optical disk substrate, a thickness t_5 of the optical disk substrate satisfies the following relationship (10) when the aspheric profile of the middle region is optimized so that the spherical aberration is corrected with respect to the thickness t_5 of the optical substrate, and the outer circumference region is formed with a difference in level corresponding to an integral multiple of the optical path length in the direction of an axis with respect to the inner circumference region,

wherein the objective lens satisfies the following relationships (11) to (13)

$$1. \quad 0 < t_5 < 1.4 \quad (10)$$

$$t_1 < t_2 \quad (11)$$

$$0.35 < NA_2 < 0.43 \quad (12)$$

$$0.03 < NA_3 - NA_2 < 0.1 \quad (13)$$

wherein t_1 denotes a thickness of the first optical disk substrate, t_2 denotes a thickness of the second optical disk substrate, NA_2 denotes a NA of the objective lens at the boundary between the inner circumference region and the middle region, and NA_3 denotes a NA of the objective lens at the boundary between the middle region and the outer circumference region.

13. The objective lens for an optical disk according to claim 12, wherein the focal position in which a wavefront aberration of the inner circumference region is minimized and the focal position in which a wavefront aberration of the outer circumference region is minimized are the same when light beams are focused through the second optical disk substrate.

14. The objective lens for an optical disk according to claim 12, wherein the third order spherical aberration component S_3 of the wavefront aberration in the ranges of the inner circumference region and the middle region is approximately 0 when light beams are focused through the second optical disk.

15. The objective lens for an optical disk according to claim 12, wherein the boundary in which the inner circumference region is connected to the middle region does not have a difference in level.

16. The objective lens for an optical disk according to claim 12, wherein the boundary between the middle region and the outer circumference region is provided at the intersection point of the profiles of the middle region and the outer circumference region.

17. The objective lens for an optical disk according to claim 12, wherein both the boundary in which the inner circumference region is connected to the middle region and the boundary in which the middle region is connected to the outer circumference region do not have a difference in level.

18. The objective lens for an optical disk according to claim 12, which is formed by glass molding or plastic molding.

19. An optical head device comprising two light sources, a focusing means for focusing light beams emitted from the two light sources onto an information medium surface through first and second optical disk substrates each having a thickness corresponding to the respective light sources, a light flux separating means for separating light fluxes modulated at the information medium, and a light receiving means for receiving the light beams modulated at the information medium, wherein the focusing means is the objective lens for an optical disk according to claim 1, 7, or 12.

20. An optical information recording and reproducing apparatus recording information on the information medium surfaces of first and second optical disk substrates each having a different thickness, or reproducing information recorded on the information medium surfaces by the use of an optical head device, wherein the optical head device according to claim 19 is used as the optical head device.

21. An objective lens for an optical disk comprising a single lens made of glass and focusing light beams into a point image through first and second optical disk substrates each having a different thickness,

at least one surface of the objective lens being divided into at least three regions by concentric circles having an optical axis as a center, the three regions including a first region including the optical axis and a second region located outermost part are rotationally symmetric aspheric surfaces, and a third region sandwiched by the first region and the second region is a toric surface having the optical axis as an axis of rotation.

22. The objective lens for an optical disk according to claim 21, wherein the third region that is the toric surface is in contact with the second region and intersects the first region.

23. The objective lens for an optical disk according to claim 21, wherein aspheric coefficients of the first region and the second region are different from each other.

24. The objective lens for an optical disk according to claim 21, wherein the toric surface is provided on the surface having a larger central radius of curvature of the lens.

25. The objective lens for an optical disk according to claim 21, wherein the third region is a toric surface obtained by rotating a circular arc with an optical axis as a center, the circular arc having a radius R satisfying the following relationship (14).

$$0.7 \text{ mm} < R < 2.5 \text{ mm} \quad (14)$$

26. The objective lens for an optical disk according to claim 21, wherein the third region is a toric surface obtained by rotating a circular arc with an optical axis as a center, the circular arc having a radius R satisfying the following relationship (15).

$$1.6 \text{ mm} < R < 2.1 \text{ mm} \quad (15)$$

27. The objective lens for an optical disk according to claim 21, wherein the width w of the third region satisfies the following relationship (16):

$$0.02 \text{ mm} < w < 0.04 \text{ mm} \quad (16)$$

28. An optical head device comprising a first light source emitting light beams having a first wavelength, a second light source emitting light beams

having a second wavelength different from the first wavelength, a focusing means for focusing light beams emitted from the first and second light sources onto an information recording medium, a first light receiving means for receiving the light beams having the first wavelength among the reflecting
5 light beams from the information recording medium and a second light receiving means for receiving the light beams having the second wavelength, wherein the focusing means is the objective lens of an optical disk according to claim 21.

10 29. A mold for molding a lens produced by grinding cemented carbide, a lens molding surface being divided into at least three regions by concentric circles having an optical axis as a center, among the three regions, a first region including the optical axis and a second region located outermost part are rotationally symmetric aspheric surfaces, the third region sandwiched by
15 the first region and the second region is a toric surface having the optical axis as an axis of rotation.

30. The mold for molding a lens according to claim 29, wherein the radius of curvature R of the toric surface having the optical axis as an axis of rotation
20 satisfies the following relationship (17).

$$0.7 \text{ mm} < R < 2.5 \text{ mm} \quad (17)$$

31. The mold for molding a lens according to claim 29, wherein the radius of curvature R of the toric surface having the optical axis as an axis of rotation
25 satisfies the following relationship (18).

$$1.6 \text{ mm} < R < 2.1 \text{ mm} \quad (18)$$

32. A method for working a mold for molding a lens, comprising: grinding a lens molding surface divided into at least three regions by concentric circles
30 having an optical axis as a center, among the three regions, a first region including the optical axis and a second region located outermost part being rotationally symmetric aspheric surfaces, the third region sandwiched by the first region and the second region being a toric surface having the optical axis as an axis of rotation by the use of a diamond grindstone, wherein a radius of
35 the diamond grindstone used for the grinding work is the same as or smaller than the radius of curvature of the toric surface.

33. The method for working a mold for molding a lens according to claim 32, wherein the radius R of the diamond grindstone satisfies the following relationship (19):

$$0.7 \text{ mm} < R < 2.5 \text{ mm} \quad (19)$$

34. The method for working a mold for molding a lens according to claim 32, wherein the radius R of the diamond grindstone satisfies the following relationship (20):

$$1.6 \text{ mm} < R < 2.1 \text{ mm} \quad (20)$$

35. A profile measuring device comprising a precision stage, a controller for controlling the precision stage, a length measuring means, a means for inputting design profile data, and a means for outputting a difference between the design profile data and measuring data, wherein as the design profile data, a first rotationally symmetric aspheric surface is used in the region where the distance from the optical axis less than the radius h_1 , a second rotationally symmetric aspheric surface is used in the region where the distance from the optical axis is not less than the radius h_2 , and a toric surface having the optical axis as a rotationally symmetric axis is used in the region between the radius h_1 and the radius h_2 .

ABSTRACT

An objective lens for an optical disk including one lens and capable of satisfying an excellent focusing property on any of two kinds of optical disks each having a different thickness. The objective lens (2) is formed of a single lens having aspheric surfaces on both sides with the surface (3) at the side of the light source a rotationally symmetric aspheric surface. Furthermore, the surface at the side of the optical disk (6) of the objective lens (2) is divided into an inner circumference region (4) and an outer circumference region (5) and a surface (7) forming the difference in level of about $0.3 \mu\text{m}$ that is provided in parallel to the optical axis (in the direction of the optical axis) at the boundary between the inner circumference region (4) and the outer circumference region (5). The spherical aberration is corrected by the inner circumference region (4) and outer circumference (5) of the objective lens (2) corresponding to the optical disks having a different thickness.

(19) 世界知的所有権機関
国際事務局(43) 国際公開日
2000年12月28日 (28.12.2000)

PCT


(10) 国際公開番号
WO 00/79322 A1

- (51) 国際特許分類: G02B 13/00, 13/18, G11B 7/135, G01B 21/20, C03B 11/08
- (72) 発明者; および
(75) 発明者/出願人 (米国についてののみ): 田中康弘 (TANAKA, Yasuhiro) [JP/JP]; 〒659-0031 兵庫県芦屋市新浜町2-5-303 Hyogo (JP). 山形道弘 (YAMAGATA, Michihiro) [JP/JP]; 〒536-0011 大阪府大阪市城東区放出西1丁目2-59-710 Osaka (JP). 笹埜智彦 (SASANO, Tomohiko) [JP/JP]; 〒564-0001 大阪府吹田市岸部北3-9-12 Osaka (JP).
- (126) 国際公開の言語: 日本語
- (127) 優先権データ:
特願平11/177177 1999年6月23日 (23.06.1999) JP
特願平11/256686 1999年9月10日 (10.09.1999) JP
- (74) 代理人: 池内寛幸, 外 (KEUCHI, Hiroyuki et al.); 〒530-0047 大阪府大阪市北区西天満4丁目3番25号 梅田ブラザビル401号室 Osaka (JP).
- (71) 出願人 (米国を除く全ての指定国について): 松下電器産業株式会社 (MATSUSHITA ELECTRIC INDUSTRIAL CO., LTD.) [JP/JP]; 〒571-8501 大阪府門真市大字門真1006番地 Osaka (JP).
- (81) 指定国 (国内): CA, KR, US.
- (84) 指定国 (広域): ヨーロッパ特許 (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).

[続葉有]

(54) Title: OBJECTIVE FOR OPTICAL DISK, OPTICAL HEAD DEVICE AND OPTICAL INFORMATION RECORDING/REPRODUCING APPARATUS BOTH COMPRISING THE SAME, MOLD FOR FORMING LENS, METHOD FOR MACHINING MOLD FOR FORMING LENS, AND SHAPE MEASURING INSTRUMENT

(54) 発明の名称: 光ディスク用対物レンズ、それを用いた光ヘッド装置及び光学情報記録再生装置、並びにレンズ成形用金型、レンズ成形用金型の加工方法及び形状計測装置



(57) Abstract: An objective for an optical disk constituted of a single lens and exhibiting a good light focusing characteristic corresponding to either of the two types of optical disk having different substrate thicknesses. An objective (2) is made up of a single bi-aspherical lens. The face (3) on the light source side is a rotationally-symmetric aspherical surface; the face on the optical disk (6) side is divided into an inner area (4) and an outer area (5). Along the boundary between the inner and outer areas (4, 5), a step

[続葉有]




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6





FIG. 7



F I G . 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12





FIG. 13



F I G. 1 4




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27




FIG. 28

1

MERCHANT & GOULD P.C.

United States Patent Application

COMBINED DECLARATION AND POWER OF ATTORNEY

As a below named inventor I hereby declare that: my residence, post office address and citizenship are as stated below next to my name; that

I verily believe I am the original, first and sole inventor (if only one name is listed below) or a joint inventor (if plural inventors are named below) of the subject matter which is claimed and for which a patent is sought on the invention entitled: OBJECTIVE LENS FOR OPTICAL DISK, OPTICAL HEAD DEVICE AND OPTICAL INFORMATION RECORDING AND REPRODUCING APPARATUS USING THE SAME, AND MOLD FOR MOLDING LENS, METHOD FOR WORKING THE MOLD FOR MOLDING LENS, AND PROFILE MEASURING DEVICE FOR MEASURING PROFILE OF THE MOLD FOR MOLDING LENS

The specification of which

- a. ☐ is attached hereto
 b. ☒ was filed on _____ as application serial no. _____ and was amended on _____ (if applicable) (in the case of a PCT-filed application) described and claimed in international no. PCT/JP00/04076 filed June 21, 2000 and as amended on _____ (if any), which I have reviewed and for which I solicit a United States patent.

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the patentability of this application in accordance with Title 37, Code of Federal Regulations, § 1.56 (attached hereto).

I hereby claim foreign priority benefits under Title 35, United States Code, § 119/365 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on the basis of which priority is claimed:

- a. ☐ no such applications have been filed.
 b. ☒ such applications have been filed as follows:

FOREIGN APPLICATION(S), IF ANY, CLAIMING PRIORITY UNDER 35 USC § 119			
COUNTRY	APPLICATION NUMBER	DATE OF FILING (day, month, year)	DATE OF ISSUE (day, month, year)
Japan	11-177177	23 June 1999	
Japan	11-256686	10 September 1999	
ALL FOREIGN APPLICATION(S), IF ANY, FILED BEFORE THE PRIORITY APPLICATION(S)			
COUNTRY	APPLICATION NUMBER	DATE OF FILING (day, month, year)	DATE OF ISSUE (day, month, year)

I hereby claim the benefit under Title 35, United States Code, § 120/365 of any United States and PCT international application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, § 112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, § 1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application.

U.S. APPLICATION NUMBER	DATE OF FILING (day, month, year)	STATUS (patented, pending, abandoned)

I hereby claim the benefit under Title 35, United States Code § 119(e) of any United States provisional application(s) listed below:

U.S. PROVISIONAL APPLICATION NUMBER	DATE OF FILING (Day, Month, Year)

I hereby appoint the following attorney(s) and/or patent agent(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected herewith:

Albrecht, John W.	Reg. No. 40,481	Larson, James A.	Reg. No. 40,443
Anderson, Gregg I.	Reg. No. 28,828	Lasky, Michael B.	Reg. No. 29,555
Ansems, Gregory M.	Reg. No. 42,764	Liepa, Mara E.	Reg. No. 40,066
Batzli, Brian H.	Reg. No. 32,960	Lindquist, Timothy A.	Reg. No. 40,701
Beard, John L.	Reg. No. 27,612	Lynch, David W.	Reg. No. 36,204
Black, Bruce E.	Reg. No. 41,622	Marschang, Diane L.	Reg. No. 35,600
Blasdel, Thomas L.	Reg. No. 31,329	McDaniel, Karen D.	Reg. No. 37,674
Bogucki, Raymond A.	Reg. No. 17,426	McDonald, Daniel W.	Reg. No. 32,044
Bruss, Steven C.	Reg. No. 34,130	McIntyre, Iain A.	Reg. No. 40,337
Byrne, Linda M.	Reg. No. 32,404	Mueller, Douglas P.	Reg. No. 30,300
Carlson, Alan G.	Reg. No. 25,959	Nelson, Albin J.	Reg. No. 28,650
Caspers, Philip P.	Reg. No. 33,227	Pauly, Daniel M.	Reg. No. 40,123
Chiapetta, James R.	Reg. No. 39,634	Phillips, John B.	Reg. No. 37,206
Clifford, John A.	Reg. No. 30,247	Plunkett, Theodore	Reg. No. 37,209
Cochran, William W.	Reg. No. 26,652	Pytel, Melissa J.	Reg. No. 25,767
Daignault, Ronald A.	Reg. No. 25,968	Reich, John C.	Reg. No. 37,703
Daley, Dennis R.	Reg. No. 34,994	Reiland, Earl D.	Reg. No. 25,767
Dalglisch, Leslie E.	Reg. No. 40,579	Rittmaster, Ted R.	Reg. No. 32,933
Daulton, Julie R.	Reg. No. 36,414	Schmaltz, David G.	Reg. No. 39,828
DeVries Smith, Katherine M.	Reg. No. 42,157	Schuman, Mark D.	Reg. No. 31,197
DiPietro, Mark J.	Reg. No. 28,707	Schumann, Michael D.	Reg. No. 30,422
Edell, Robert T.	Reg. No. 20,187	Scull, Timothy B.	Reg. No. 42,137
Epp Ryan, Sandra	Reg. No. 39,667	Sebal, Gregory A.	Reg. No. 33,280
Funk, Steven R.	Reg. No. 37,830	Skoog, Mark T.	Reg. No. 40,178
Glance, Robert J.	Reg. No. 40,620	Soderberg, Richard	Reg. No. P. 43,352
Gølla, Charles E.	Reg. No. 26,896	Sumner, John P.	Reg. No. 29,114
Gorman, Alan G.	Reg. No. 38,472	Sumners, John S.	Reg. No. 24,216
Gould, John D.	Reg. No. 18,223	Tellekson, David K.	Reg. No. 32,314
Gregson, Richard	Reg. No. 41,804	Trembath, Jon R.	Reg. No. 38,344
Gresens, John J.	Reg. No. 33,112	Underhill, Albert L.	Reg. No. 27,403
Hamre, Curtis B.	Reg. No. 29,165	Vandenburgh, J. Derek	Reg. No. 32,179
Hillson, Randall A.	Reg. No. 31,838	Vradenburgh, Anna M.	Reg. No. 39,868
Hölzer, Jr., Richard J.	Reg. No. 42,668	Welter, Paul A.	Reg. No. 20,890
Johnston, Scott W.	Reg. No. 39,721	Wahl, John R.	Reg. No. 33,044
Kadievitch, Natalie D.	Reg. No. 34,196	Whipps, Brian	Reg. No. 43,261
Kästlelic, Joseph M.	Reg. No. 37,160	Wickhem, J. Scot	Reg. No. 41,376
Kettelberger, Denise	Reg. No. 33,924	Williams, Douglas J.	Reg. No. 27,054
Khearl, Homer L.	Reg. No. 21,197	Witt, Jonelle	Reg. No. 41,980
Kowalchyk, Alan W.	Reg. No. 31,535	Wood, William J.	Reg. No. 42,236
Kowalchyk, Katherine M.	Reg. No. 36,848	Xu, Min S.	Reg. No. 39,536
Kubota, Glenn M.	Reg. No. 44,197		
Lacy, Paul E.	Reg. No. 38,946		

I hereby authorize them to act and rely on instructions from and communicate directly with the person/assignee/attorney/firm/organization who/which first sends/sent this case to them and by whom/which I hereby declare that I have consented after full disclosure to be represented unless/until I instruct Merchant & Gould P.C. to the contrary.

Please direct all correspondence in this case to Merchant & Gould P.C. at the address indicated below:

Merchant & Gould P.C.
P.O. Box 2903
Minneapolis, MN 55402-0903

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

2	Full Name Of Inventor	Family Name TANAKA	First Given Name Yasuhiro	Second Given Name
0	Residence & Citizenship	City Hyogo JP	State or Foreign Country Japan	Country of Citizenship Japan
1	Post Office Address	Post Office Address 2-5-303, Niihamacho, Ashiya-shi		State & Zip Code/Country Hyogo 659-0031/JAPAN
Signature of Inventor 201:			Date:	
			Yasuhiro Tanaka February 7, 2001	
2	Full Name Of Inventor	Family Name YAMAGATA	First Given Name Michihiro	Second Given Name
0	Residence & Citizenship	City Osaka JP	State or Foreign Country Japan	Country of Citizenship Japan
2	Post Office Address	Post Office Address 2-59-710, Hanatennishi 1-chome, Joto-ku, Osaka-shi		State & Zip Code/Country Osaka 536-0011/JAPAN
Signature of Inventor 202:			Date:	
			Michihiro Yamagata February 7, 2001	
2	Full Name Of Inventor	Family Name SASANO	First Given Name Tomohiko	Second Given Name
0	Residence & Citizenship	City Osaka JP	State or Foreign Country Japan	Country of Citizenship Japan
3	Post Office Address	Post Office Address 3-9-12, Kishibekita Suita-shi		State & Zip Code/Country Osaka 564-0001/JAPAN
Signature of Inventor 203:			Date:	
			Tomohiko Sasano February 7, 2001	

§ 1.56 Duty to disclose information material to patentability.

(a) A patent by its very nature is affected with a public interest. The public interest is best served, and the most effective patent examination occurs when, at the time an application is being examined, the Office is aware of and evaluates the teachings of all information material to patentability. Each individual associated with the filing and prosecution of a patent application has a duty of candor and good faith in dealing with the Office, which includes a duty to disclose to the Office all information known to that individual to be material to patentability as defined in this section. The duty to disclose information exists with respect to each pending claim until the claim is canceled or withdrawn from consideration, or the application becomes abandoned. Information material to the patentability of a claim that is canceled or withdrawn from consideration need not be submitted if the information is not material to the patentability of any claim remaining under consideration in the application. There is no duty to submit information which is not material to the patentability of any existing claim. The duty to disclose all information known to be material to patentability is deemed to be satisfied if all information known to be material to patentability of any claim issued in a patent was cited by the Office or submitted to the Office in the manner prescribed by §§ 1.97(b)-(d) and 1.98. However, no patent will be granted on an application in connection with which fraud on the Office was practiced or attempted or the duty of disclosure was violated through bad faith or intentional misconduct. The Office encourages applicants to carefully examine:

- (1) prior art cited in search reports of a foreign patent office in a counterpart application, and
- (2) the closest information over which individuals associated with the filing or prosecution of a patent application believe any pending claim patentably defines, to make sure that any material information contained therein is disclosed to the Office.

(b) Under this section, information is material to patentability when it is not cumulative to information already of record or being made of record in the application, and

- (1) It establishes, by itself or in combination with other information, a prima facie case of unpatentability of a claim;
- (2) It refutes, or is inconsistent with, a position the applicant takes in:
 - (i) Opposing an argument of unpatentability relied on by the Office, or
 - (ii) Asserting an argument of patentability.

A prima facie case of unpatentability is established when the information compels a conclusion that a claim is unpatentable under the preponderance of evidence, burden-of-proof standard, giving each term in the claim its broadest reasonable construction consistent with the specification, and before any consideration is given to evidence which may be submitted in an attempt to establish a contrary conclusion of patentability.

(c) Individuals associated with the filing or prosecution of a patent application within the meaning of this section are:

- (1) Each inventor named in the application;
- (2) Each attorney or agent who prepares or prosecutes the application; and

(3) Every other person who is substantively involved in the preparation or prosecution of the application and who is associated with the inventor, with the assignee or with anyone to whom there is an obligation to assign the application.

(d) Individuals other than the attorney, agent or inventor may comply with this section by disclosing information to the attorney, agent, or inventor.